

Product Name

**Qs**  
(Linear)

Technical description

Adjustable floodlight suitable for wall or ceiling application, designed to produce direct or indirect light. It has a low visual impact. Body in die-cast aluminum alloy UNI EN 1706 (Low copper content) painted with polyester powder. Supplied with a painted galvanised steel bracket. Screws made of AISI 304 stainless steel. Silicone gaskets. LED light source (lumileds), colour temperature (4000 K Neutral White). High coefficient of performance chromatic CRI>80. Optic optical PC.



Supply

Driver included linear.  
Input voltage 230 V AC 50Hz.  
Temperature -40° +45°

Installation

Wall and ceiling.

Applications

Big boards, facades decoration, shop windows.

Size (mm)



155 x 171 x 32

Colour

Dark grey **4**

Decay of the luminous flux

≤50.000 hr L85B15



C0 / C180    C90 / C270

Code	Source	Power	Lm (Output)	Lm (Tc=25°)	Temperature	CRI	Beams	Colour
<b>L00QS4060L140020</b>	LED	20 W	1980 lm	2900 lm	4000 K	>80	60°	Dark grey

Accessories



Pole connection B  
LKITA00000040109



Fast connector  
IP 3 poles  
LKITA0000000003



Ground spike  
support kit  
LKITA0000000022

LANZINI indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.