

## Data sheet

Commercial Art.No.: 92.050.3353.0

distributor GST18I5VK2A1TBGV 3 WS

gesis® CLASSIC T-Distributor for phase selection L3, with fastening option to 07.413.6853.1/0, cascadable, number of poles 5, rated voltage 250 V / 400 V, rated current 20 A, number of inputs 1, number of outputs 2, color of coding/ contact carrier white



certificates / approvals



## Technical data

### general

rated current	20 A
rated voltage	250 V / 400 V
rated impulse voltage	4 kV
pollution degree	2
mechanical coding	code 1
lockable	self-locking (unlocking by tool)
color of coding/ contact carrier	white
marking of poles	3, N, PE, 2, 1
RAL-number coding/insert connector	9016

### model

number of inputs	1
number of outputs	2
type of fastening	yes
degree of protection (IP)	IP40
type of distributor	T-Distributor for phase selection

### material

housing material	polyamide
halogen free	yes
contact material	CuZn
fire load	0.133 kWh/St
insulation components continuous temperature	100 °C
surface finish	tin-plated

### dimensions

length	57.3 mm
width	47.9 mm

height	44.8 mm
--------	---------

**classification**

ECLASS 11	
ECLASS 8.1	27440603
ETIM 9.0	EC002567
ETIM 8.0	EC002567
ETIM 7.0	EC002567
ETIM 6.0	EC002567
ETIM 5.0	EC002567
ETIM 4.0	EC002567

**product compliance**

ROHS conformity status	compliant/exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1