



# PRODUCT DATASHEET

## SMART+ Wifi Neon Flex 3M RGB + TW

Smart+ Neon Flex Multicolor | Decorative LED Strips for outdoor use with WiFi technology and homogenous illumination



---

### Areas of application

- Gardens, balconies and other outdoor areas
- Living areas
- Indirect and direct lighting

---

### Product benefits

- Easy and quick installation
- Uses multi color and cold or warm white light for most flexible lighting scenes

---

### Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Flexible, bendable LED strips
- Type of protection: IP44



## TECHNICAL DATA

### Electrical data


Nominal wattage	15.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	120.000 mA
Power factor $\lambda$	> 0.5
Protection class	II
Operating mode	External LED driver

### Photometrical data

Luminous flux	520 lm
Total luminous flux of contained light sources	1260 lm
Luminous efficacy	35 lm/W
Color temperature	2700...6500 K
Reference control setting of contained light source (Kelvin)	3500 K
Light color (designation)	RGBTW
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdc <sub>m</sub>
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	110 °

### Dimensions & Weight

Length	3000.00 mm
Width	17.50 mm
Height	9.80 mm
Product weight	670.00 g



SMART WIFI NEON FLEX 3M  
RGBTW IP44

### Materials & Colors

Product color	Transparent
Body material	Silicone
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	-20...40 °C
Type of connection	Plug type C (EU)
Type of protection	IP44
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Mounting location	All surfaces
Application environment	Outdoor
LED module replaceable	Not replaceable
With light source	Yes

### Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000



### Certificates & Standards

Standards	CE / EAC
-----------	----------

### EQUIPMENT / ACCESSORIES

- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)
- Complete mounting and connecting accessories included

### DOWNLOAD DATA

Documents and certificates	Document name
 User Instruction	SMART+ WIFI NEON FLEX
 Declarations of conformity	SMART WIFI NEON FLEX 3M RGBTW IP44

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075504783	Folding box 1	64 mm x 299 mm x 275 mm	952.00 g	5.26 dm <sup>3</sup>
4058075504790	Shipping box 4	570 mm x 314 mm x 168 mm	4957.00 g	30.07 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

– Further information and frequently asked questions (FAQs) at [www.ledvance.com/consumer/smart/faq](http://www.ledvance.com/consumer/smart/faq)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.