

# PRODUCT DATASHEET SMART+ Wifi Floodlight 20W RGB + W + RC

SMART+ MULTICOLOR WITH REMOTE CONTROL | Floodlights with WiFi technology



## Areas of application

- Building facades

## **Product benefits**

- Easy and quick installation
- Colorful garden lighting with smart and intelligent control options
- Combines the functionality of general lighting and mood lighting

## **Product features**

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Color temperature: 3,000 K (Warm White)
- Network protocol: WiFi
- Mounting bracket for up to 180° tilting
- Type of protection: IP65
- Connection via 0.5 m cable, wiring required



July 08, 2024, 17:53:50 SMART+ Wifi Floodlight 20W RGB + W + RC

## **TECHNICAL DATA**

# Electrical data


Nominal wattage	20 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	90.000 mA
Inrush current	15 A
Max. number of luminaires per miniature circuit breaker C10	15
Power factor $\lambda$	> 0.90
Protection class	I
Operating mode	Mains voltage

## Photometrical data

Luminous flux	1600 lm
Luminous efficacy	63 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥80
Standard deviation of color matching	< 6 sdcm
Flickering metric (Pst LM)	≤1 %
Stroboscope effect metric (SVM)	≤0.4
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	100 °

# **Dimensions & Weight**

Length	152.00 mm
Width	125.00 mm
Height	28.00 mm
Product weight	419.00 g





SMART WIFI REMOTE CONTROL

# SMART OUTD WIFI FLOOD20W REM RGBWDG

#### Materials & Colors

Product color	Dark gray
Housing color	Dark gray
Body material	Aluminum
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-20+40 °C	
Temperature range at storage	-20+80 °C	
Type of connection Terminal, 3-Pole (L, N, PE)		
Type of protection	IP65	
Protection class IK (shock resistance)	IK05	
Dimmable	Yes	
Type of dimming	WiFi	
Mounting type	Surface	
Mounting location	Wall	
Application environment	Outdoor	
LED module replaceable	Not replaceable	
With light source	Yes	

# Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	30000

# **Emergency lighting**

Type of emergency light operation	Non-maintained
-----------------------------------	----------------

None
-
-
No

# Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No

#### EQUIPMENT / ACCESSORIES

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

## DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User Instruction	Smart Wifi Flood RGBW and Remote	
PDF	Legal information	Legal insert SMART OUTD WIFI FLOOD	
PDF	Declarations of conformity	SMART OUTD WIFI FLOOD20W REM RGBWDGLEDV	
PDF	Declarations Of Conformity UKCA	SMART OUTD WIFI FLOOD	

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075576674	Folding box 1	204 mm x 40 mm x 164 mm	621.00 g	1.34 dm <sup>3</sup>
4058075576681	Shipping box 6	264 mm x 229 mm x 208 mm	4176.00 g	12.57 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **References / Links**

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.