

PRODUCTINFORMATIEBLAD DALI LS/PD CI

DALI LS/PD CI | Sensoren voor lichtmanagementsystemen



Toepassingsgebieden

- Classrooms
- Conference rooms
- Corridors
- Individual offices
- Open-plan offices
- Restaurants
- Shop lighting
- Suitable for indoor applications

Productvoordelen

- Can be addressed via DALI
- Daylight-dependent control with automatic shutdown in adequate daylight
- Multiple sensors can be networked
- Simple installation
- Sensor integration in DALI
- Power supply from DALI
- Presence detection angle adjustable between 40...90° via integrated shutters
- DALI based light management system integrable into building management systems

Productkenmerken

- Mounting height: 2...5 m
- Presence detection via passive IR element
- Light sensor operating range: 20...800 lx (measured at sensor)
- Daylight-dependent regulation and presence-dependent control of light
- Direct connection to DALI
- Function indicator with two-color LED


– Ceiling installation adapter

TECHNISCHE GEGEVENS

ELEKTRISCHE GEGEVENS

Nominale spanning	16 V
Netfrequentie	0 Hz

AFMETINGEN & GEWICHT



Lengte	80,00 mm
Breedte	80,00 mm
Breedte (incl. ronde armaturen)	80.00 mm
Hoogte	55,00 mm ¹⁾
Hoogte (incl. cylin. armaturen)	55.00 mm
Diameter	80,0 mm
Product gewicht	95,00 g

1) h1

KLEUREN & MATERIALEN

Kleur van het product	Wit
-----------------------	-----

TEMPERATUREN & BEDRIJFSOMSTANDIGHEDEN

Omgevingstemperatuur bereik	-20...+50 °C
-----------------------------	--------------

MOGELIJKHEDEN

Dimbaar	Nee
Maximale inbouwhoogte	5 m
Detectie zone	6 m ¹⁾
Detectie hoek	40...90 °
Type montage	Verzonken
Bereik van de lichtsensor	20...800 lx

1) Maximale diameter





CERTIFICATEN & NORMEN

Keurmerken	CE
Veiligheidsklasse	II
Type bescherming	IP20

Technische uitrusting

– Suitable for many OSRAM DALI control systems

DOWNLOADS

Documenten en certificaten	Naam document
 User Instruction	538500_Mounting instructions DALI LS/PD CI
 User Instruction	DALI LS/PD CI
 Declarations of conformity	EU Declaration of Conformity 2019_9C1_2874588_EN_09
CAD/BIM-bestanden	Naam document
 CAD_STEP_3D	DALI LS PD CI STEP 220620

LOGISTIEKE GEGEVENS

Productcode	Verpakkingseenheid (stuks per verpakking)	Afmetingen (lengte x breedte x hoogte)	Brutogewicht	Volume
4052899930292	BAG 1	152 mm x 111 mm x 73 mm	95.00 g	1.23 dm ³
4052899930308	Verzenddoos 10	217 mm x 217 mm x 180 mm	1272.00 g	8.48 dm ³

De genoemde productcodes beschrijven de kleinste hoeveelheid die besteld kan worden. Eén verzendeenheid kan bestaan uit één of meer afzonderlijke producten. Bij het plaatsen van een order enkele of veelvoud van de verpakkingseenheid invoeren.

DISCLAIMER

Onder voorbehoud van verandering zonder kennisgeving. Fouten en drukfouten voorbehouden. Zorg ervoor dat u de meest recente versie gebruikt.