

PRODUCT DATASHEET DALI PRO Sensor Coupler

DALI PRO Sensor Coupler | Sensors for light management systems



Areas of application

- Connection of light and presence sensors in DALI systems
- Ceiling or independent installation via ECO CI KIT possible

Product benefits


- Power supply from DALI

TECHNICAL DATA

Electrical data

Nominal wattage	0.10 W	
Nominal voltage	20 V	
Mains frequency	0 Hz	

Dimensions & Weight



Length	118.00 mm
Mounting hole spacing, length	110,0 mm
Width	30.00 mm
Height	21.00 mm
Product weight	35.00 g

Temperatures & operating conditions

Ambient temperature range	0+50 °C
---------------------------	---------

Additional product data

Number of control outputs	1
---------------------------	---

Capabilities

Dimmable	No
Dimming interface	DALI
Number of control outputs	1
Type of installation	Luminaire integration/Ceiling integration

Certificates & Standards

Approval marks – approval	CE
Protection class	II
Type of protection	IP20

EQUIPMENT / ACCESSORIES

- Suitable for all light and presence sensors from the MULTI 3 range
- Suitable for many OSRAM DALI control systems

DOWNLOAD DATA

	Documents and certificates	Document name
POF	User Instruction	334249_Technical instructions
PDF	User Instruction	DALI Sensor Coupler LS/PD
PDF	Declarations of conformity	334811_Declaration of conformity – DALI PRO CONT-4 – DALI PRO PB Coupler – DALI PRO Sen
PDF	Declarations of conformity	EC-DoC LMS Sensor Coupler and Sensor 9C1-3402820-EN-02 2019

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321379269	Folding box 1	128 mm x 27 mm x 37 mm	49.00 g	0.13 dm ³
4008321379276	Shipping box 25	200 mm x 140 mm x 147 mm	1268.00 g	4.12 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.