

PRODUCT DATASHEET DIM MCU G2

DIM MCU | Light management systems



Areas of application

- Conference rooms
- Restaurants
- Shop lighting

Product benefits

- Intuitive manual dimming and switching
- Individual setting of minimal brightness level

Product features


- Switching load contact: 250 V/6 A (10 1-lamp or 5 2-lamp ECGs)
- Cover and rotary knob in cream white

TECHNICAL DATA

Electrical data

Nominal voltage	230 V
Mains frequency	50/60 Hz

Dimensions & Weight



Length	71.00 mm
Mounting hole spacing, length	60,0 mm
Width	71.00 mm
Height	40.00 mm
Product weight	88.00 g

Colors & materials

Temperatures & operating conditions

Ambient temperature range -20+50 °C	
-------------------------------------	--

Capabilities

Dimmable	Yes
Dimming interface	110 V
Type of installation	Integrated in flush device box

Certificates & Standards

Approval marks – approval	CE / EAC / UKCA
Protection class	II
Type of protection	IP20

EQUIPMENT / ACCESSORIES

- Suitable for up to 50 electronic control gears (external load contact required)
- Flexible expansion via external load contact and via signal amplifier DIM SA
- Cover and rotary knob included

DOWNLOAD DATA

	Documents and certificates	Document name	
POF	User Instruction	22010927 DIM MCU G2	
POF	Declarations of conformity	DIM MCU DALI MCU TW	
POF	Declarations Of Conformity UKCA	DIM MCU DALI MCU TW G2	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4062172224642	Folding box 1	85 mm x 85 mm x 65 mm	133.00 g	0.47 dm ³
4062172224659	Shipping box 48	362 mm x 270 mm x 288 mm	6820.00 g	28.15 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.