

## PRODUCT DATASHEET OT SLIM 60/220-240/24

CV Power supplies 24 V | CV Power supplies 24 V



---

### Areas of application

- Facades, public squares, cruise ships
- Signage
- Suitable for indoor and outdoor installations

---

### Product benefits

- Installation in cold and hot environments
- Very stable output power
- High electrical reversible short-circuit, overload, overtemperature protection
- Independent installation possible

---

### Product features


- Type of protection: IP20
- Wide operating temperature range: -20...+50 °C
- Lifetime: up to 50,000 h (temperature at max.  $t_c$ )

## TECHNICAL DATA

### Electrical data

Nominal wattage	68.00 W
Nominal output power	60 W
Nominal voltage	220...240 V
Nominal output voltage	24.2 V
Input voltage AC	195.5...276 V
Input voltage DC	176...250 V
U-OUT (working voltage)	24 V
Inrush current	40 A
Mains frequency	50/60 Hz
Total harmonic distortion	< 5 %
Power factor $\lambda$	0.95
Device power loss	8.2 W
Max. ECG no. on circuit breaker 10 A (B)	11
Max. ECG no. on circuit breaker 16 A (B)	17
Max. ECG no. on circuit breaker 25 A (B)	16
Surge capability (L-N)	1 kV
Galvanic isolation	SELV

### Dimensions & Weight



Length	338.00 mm
Mounting hole spacing, length	290,0 mm
Width	30.00 mm
Height	17.50 mm
Cable cross-section, input side	0.75...1.5 mm <sup>2</sup>
Cable cross-section, output side	0.75...1.5 mm <sup>2</sup>
Wire preparation length, input side	5,0 mm
Wire preparation length, output side	5,0 mm
Product weight	170.00 g

### Colors & materials

Casing material	Plastic
-----------------	---------

Body material	Plastic
---------------	---------

**Temperatures & operating conditions**

Ambient temperature range	-25...+45 °C
Maximum temperature at tc test point	70 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5...85 % <sup>1)</sup>

<sup>1)</sup> Maximum 56 days/year at 85 %

**Lifespan**

ECG lifetime	50000 h
--------------	---------

**Capabilities**

Dimmable	No
Overload protection	Automatic reversible
Short-circuit protection	Automatic reversible
Suitable for fixtures with prot. class	I / II
Type of connection, output side	Screw terminal

**Certificates & Standards**

Approval marks – approval	CE / CB / ENEC / CCC / EAC / RCM / BIS
Standards	Acc. to IEC 61347-2-13 / Acc. to IEC 62384 / Acc. to EN 55015 / Acc. to IEC 61000-3-2 / Acc. to IEC 61000-3-3
Protection class	II
Type of protection	IP20


**LOGISTICAL DATA**

Temperature range at storage	-40...+85 °C
------------------------------	--------------

**ADDITIONAL PRODUCT INFORMATION**

- EMI pass verified with wire length of 2 m, from the ECG to the LED module at full load.
- Wiring longer than 2 m from ECG to LED module is possible, but site installation conditions may interfere with EMI with these longer cables. EMI is therefore not verified in this condition.
- For wires longer than 2 m, the appropriate cable cross section must be carefully selected to reduce voltage drop.

**DOWNLOAD DATA**

Documents and certificates	Document name
 User Instruction	14614288 OT SLIM

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4062172135856	Unpacked 1			
4062172135863	Shipping box 30	350 mm x 192 mm x 145 mm	5560.00 g	9.74 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.