


PRODUCT DATASHEET

LS AY -CSD/P2

Connectors for LED Strips PFM and VAL | Connector for LED Strips



Areas of application

- General indoor illumination

Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

TECHNICAL DATA

Electrical data

Nominal voltage	24 V
Nominal current	5000 mA

Dimensions & Weight

Length	20.9 mm
Width	10.5 mm
Height	4.5 mm
Cable cross-section, input side	0.5 mm ²
Product weight	1.5 g

Colors & materials

Product color	White
---------------	-------

Temperatures & operating conditions

Ambient temperature range	-20...+55 °C
---------------------------	--------------


Certificates & Standards

Type of protection	IP00
--------------------	------

LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

DOWNLOAD DATA

Tender texts	Document name
 Tender documents	Connectors for LED Strips PFM and VAL CSDP2-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075727526	BAG 2	80 mm x 120 mm x 5 mm	4.00 g	0.05 dm ³
4058075727533	Shipping box 100	120 mm x 100 mm x 120 mm	248.00 g	1.44 dm ³
4058075727540	Shipping box 1,000	525 mm x 140 mm x 270 mm	2871.00 g	19.85 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.