

# PRODUCT DATASHEET

## LS AY -CP/P2/500/P

Connectors for LED Strips PFM and VAL | Connector for LED Strips

---

### Areas of application

- General indoor illumination



---

### Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

## TECHNICAL DATA

### Electrical data

Nominal voltage	24 V
Nominal current	5000 mA

### Dimensions & Weight

Length	526 mm
Cable length	500 mm
Width	15.0 mm
Height	7 mm
Cable cross-section, input side	0.5 mm <sup>2</sup>
Product weight	11.00 g

### Colors & materials

Product color	Transparent
---------------	-------------

### Temperatures & operating conditions

Ambient temperature range	-20...+55 °C
---------------------------	--------------


### Certificates & Standards

Type of protection	IP67
--------------------	------

## LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

## DOWNLOAD DATA

Tender texts	Document name
 Tender documents	Connectors for LED Strips PFM and VAL CPP2500P-EN

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075727465	BAG 2	80 mm x 120 mm x 5 mm	23.00 g	0.05 dm <sup>3</sup>
4058075727472	Shipping box 100	180 mm x 100 mm x 180 mm	1229.00 g	3.24 dm <sup>3</sup>
4058075727489	Shipping box 1,000	520 mm x 380 mm x 210 mm	13058.00 g	41.50 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.