

PRODUCT DATASHEET

LS AY -CP/P2/500

Connectors for LED Strips PFM and VAL | Connector for LED Strips

Areas of application

- General indoor illumination



Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

TECHNICAL DATA

Electrical data

Nominal voltage	24 V
Nominal current	5000 mA

Dimensions & Weight

Length	516 mm
Cable length	500 mm
Width	10.5 mm
Height	4.5 mm
Cable cross-section, input side	0.5 mm ²
Product weight	9.5 g

Colors & materials

Product color	White
---------------	-------

Temperatures & operating conditions

Ambient temperature range	-20...+55 °C
---------------------------	--------------


Certificates & Standards

Type of protection	IP00
--------------------	------

LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

DOWNLOAD DATA

	Tender texts	Document name
	Tender documents	Connectors for LED Strips PFM and VAL CPP2500-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075727403	BAG 2	80 mm x 120 mm x 5 mm	20.00 g	0.05 dm ³
4058075727410	Shipping box 100	180 mm x 100 mm x 180 mm	1079.00 g	3.24 dm ³
4058075727427	Shipping box 1,000	520 mm x 380 mm x 210 mm	11558.00 g	41.50 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.