

PRODUCT DATASHEET

HB P 190W 840 70DEG IP65

HIGH BAY GEN 4 | High-bay luminaires up to 150 lm/W and attractive UGR



PERFOR-
MANCE
CLASS

Areas of application

- Replacement for high bay luminaires with mercury vapor or metal halide lamps
- Warehouses
- Logistics halls
- Industry
- High ceiling (e.g. in shopping malls, airports, commercial buildings, lobbies)

Product benefits

- Improved UGR compared to previous generations, down to $UGR \leq 22$ in combination with reflector
- High luminous efficacy
- Energy savings of up to 64 % compared to conventional high bay luminaires
- 5 years guarantee
- Optimized weight and size due to compact design

Product features

- Different luminous flux and beam angle for mounting heights of ~ 6 m to 14 m in 4000 K or 6500 K

TECHNICAL DATA

Electrical data

| | |
|---|---------------|
| Nominal wattage | 190.00 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Nominal current | 840 mA |
| Inrush current | 50.4 A |
| Inrush current time T_{h50} | 480 μ s |
| Max. number of luminaires per miniature circuit breaker B16 | 3 |
| Max. number of luminaires per miniature circuit breaker C10 | 3 |
| Max. number of luminaires per miniature circuit breaker C16 | 5 |
| Power factor λ | ≥ 0.95 |
| Total harmonic distortion | $< 20 \%$ |
| Protection class | I |
| Operating mode | Mains voltage |

Photometrical data


| | |
|--|---------------------------|
| Luminous flux | 27000 lm |
| Luminous efficacy | 140 lm/W |
| Color temperature | 4000 K |
| Light color (designation) | Cool White |
| Color rendering index Ra | ≥ 80 |
| Standard deviation of color matching | ≤ 5 sdc _m |
| Low flicker | Yes |
| Photobiological safety group acc. to EN62778 | RG1 |
| Beam angle | 70 ° |
| UGR | ≤ 25 |

HB P 190W 840 70DEG IP65

HB P 190W 840 70DEG IP65

Dimensions & Weight

| | |
|----------------|-----------|
| Diameter | 321.00 mm |
| Height | 156.00 mm |
| Product weight | 2830.00 g |
| Cable length | 1500 mm |



HB 180W 200W 70 DEG 110 DEG

Materials & Colors

| | |
|--|--------------------|
| Product color | Black |
| Housing color | Black |
| Body material | Aluminum |
| Cover material | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 850 °C |

Application & Mounting

| | |
|--|-------------------|
| Ambient temperature range | -30...+50 °C |
| Temperature range at storage | -40...+70 °C |
| Type of connection | Cable, 3-pole |
| Type of protection | IP65 |
| Protection class IK (shock resistance) | IK08 |
| Dimmable | No |
| Mounting type | Suspended/Surface |
| Mounting location | Ceiling / Wall |
| Application environment | Indoor |
| LED module replaceable | Not replaceable |
| With light source | Yes |

Lifespan

| | |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C | 80000 h ¹⁾ |
| Lifespan L80/B10 at 25 °C | 50000 h ¹⁾ |
| Lifespan L90/B10 at 25 °C | 35000 h |
| Number of switching cycles | 200000 |

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

| | |
|-----------------------------|--------|
| ECG - Output ripple current | < 10 % |
|-----------------------------|--------|









Certificates & Standards





| | |
|--|--------------------------------------|
| Standards | CE / CB / ENEC / TÜV SÜD / EAC / EPD |
| Luminaire with limited surface temperature, "D sign" | Yes |
| Ball shot safe | No |
| EPD | LEDV-00006-V01.01-EN |









EQUIPMENT / ACCESSORIES

- Mounting hook included
- Mounting brackets, reflectors and refractors available as separate accessory

DOWNLOAD DATA

| Documents and certificates | | Document name |
|--|---------------------------------|--|
|  | User Instruction | UI HighBay Gen4 |
|  | User Instruction | UI HighBay Gen4 |
|  | Addon Technical Information | LS Insert HB P GEN4 |
|  | Legal information | Legal insert HB P GEN 4 AND HB GEN 3 |
|  | Declarations of conformity | EC Declaration HB P |
|  | Declarations Of Conformity UKCA | UKCA Declaration of Conformity HB P IP65 |
|  | Declarations Of Conformity UKCA | HB P IP65 |
|  | Certificates | ENEC Certificate HB P and HB Sensor P |

| Photometric and lighting design files | | Document name |
|--|---------------------|--------------------------|
|  | IES file (IES) | HB P 190W 840 70DEG IP65 |
|  | IES file (IES) | HB P 190W 840 70DEG IP65 |
|  | LDT file (Eulumdat) | HB P 190W 840 70DEG IP65 |
|  | LDT file (Eulumdat) | HB P 190W 840 70DEG IP65 |


| Photometric and lighting design files | | Document name |
|--|----------------------|---------------------------------------|
|  | ULD file (DIALux) | HB P 190W 840 70DEG |
|  | ROLF file (RELUX) | HB P 190W 840 70DEG IP65 |
|  | UGR file (UGR table) | HB P 190W 840 70DEG IP65 |
|  | LDC typ cone | HB P 190W 840 70DEG IP65 |
|  | LDC typ polar | HB P 190W 840 70DEG IP65 |
| CAD/BIM files | | Document name |
|  | BIM_Revit_3D | HB G4 |
|  | CAD_STEP_3D | HB G4 190W |
| Tender texts | | Document name |
|  | Tender documents | HIGH BAY GEN 4 190W 840 70DEG IP65-EN |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075692824 | Shipping box 1 | 368 mm x 368 mm x 168 mm | 3483.00 g | 22.75 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.