

# PRODUCT DATASHEET

## SF FLAT SQ SEN 330 P 19W CPS

SURFACE FLAT SQUARE SENSOR | Versatile square wall and ceiling luminaire with integrated sensor

### Areas of application

- Direct replacement for surface luminaires with integrated CFLni lamps
- Corridors
- Stairwells
- Bathrooms
- Foyers



### Product benefits

- Multiple settings for sensor range, daylight detection, hold time and DIM-level /-period by DIP switches
- Wireless (radio frequency) communication with other sensor luminaires in a distance of up to 15 m
- Assignment of up to 15 groups and cross-group interaction (leader/follower or swarm function)
- Easy upgradeability of light source, driver and sensor (EVERLOOP design)
- Highly versatile due to selectable CCT and power steps (Multi Color / Multi Lumen) on the driver
- Indoor luminaire with high luminous efficacy up to 140 lm/W
- High color consistency with SDCM 3
- Tool-free electrical connection due to push button connector
- Very homogenous light with a slight backlight effect
- For comfortable configuration the sensor can be removed from luminaire
- 5 years guarantee

### Product features

- High frequency sensor for daylight and motion detection, corridor- and grouping function
- Type of protection: IP54 (wall and ceiling)
- Impact resistance: IK08
- Lifetime (L80/B10): 100,000 h (at 25 °C), (L90/B10): 50,000 h (at 25 °C)
- Polycarbonate (PC) housing, PC-diffusor
- Ambient temperature in operation: -20...+45 °C
- Glow Wire Test according to IEC 60695-2-12: 850 °C

- 5-pole terminal block, cable cross section up to 5 x 2.5 mm<sup>2</sup>
- Through-wiring possible
- Indoor use only, not suitable for outdoor use

## TECHNICAL DATA

### Electrical data


Nominal wattage	19 W / 12 W <sup>1)</sup>
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	85.000 mA
Inrush current	13 A
Inrush current time $T_{h50}$	112 $\mu$ s
Max. number of luminaires per miniature circuit breaker B16	57
Max. number of luminaires per miniature circuit breaker C10	46
Max. number of luminaires per miniature circuit breaker C16	73
Power factor $\lambda$	> 0.90
Total harmonic distortion	< 20 %
Protection class	II
Operating mode	Integrated LED driver

<sup>1)</sup> For possible options refer to lumen/power table image


### Photometrical data

Luminous flux	2660 lm / 1660 lm <sup>1)</sup>
Luminous efficacy	140 lm/W / 138 lm/W <sup>1)</sup>
Color temperature	3000 K / 4000 K
Light color (designation)	Warm White / Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	3 sdcn
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	120 °


<sup>1)</sup> For possible options refer to lumen/power table image




SF FLAT SQ SEN 330 P 19W  
3000K 2490lm



SF FLAT SQ SEN 330 P 19W  
4000K 2660lm




SF FLAT SQ SEN 330 P 19W  
3000K 2490lm



SF FLAT SQ SEN 330 P 19W  
4000K 2660lm

Dimensions & Weight

Length	330.00 mm
Width	330.00 mm
Height	65.00 mm
Product weight	1565.00 g



SF FLAT SQ 330 19W CPS

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	850 °C

Mercury content	0.0 mg
-----------------	--------

### Application & Mounting

Ambient temperature range	-20...+45 °C
Temperature range at storage	-40...+80 °C
Type of connection	Screwless terminal
Type of protection	IP54
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Indoor
LED module replaceable	Not replaceable
With light source	Yes

### Lifespan

Lifespan L70/B50 at 25 °C	100000 h <sup>1)</sup>
Lifespan L80/B10 at 25 °C	100000 h <sup>1)</sup>
Lifespan L90/B10 at 25 °C	50000 h
Number of switching cycles	100000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Control gear

Output current	450 mA
ECG - Output ripple current	< 5 %

### Sensor

Type of sensor	Motion / Light
Sensor technology	Microwave
Sensor detection angle	120 °
Sensor controlled switching time	5 s...20 min
Detection range of motion sensor	3...7 m
Detection threshold of daylight sensor	15...150 lx





### Certificates & Standards

Standards	CE / CB / ENEC / UKCA / EAC
Luminaire with limited surface temperature, "D sign"	Yes
Ball shot safe	No

### Additional product data

Product remark	Available from September 2024
Added function	EVERLOOP / MULTI SELECT







Accessories Optional












Product image	Product name	EAN
	LISOEV 330 SQ 19W 830 840 SF FLAT	4099854312250
	SF FLAT 330 SQUARE FRAME SI	4099854292910
	DR DS SENS-P- 19/220-240/450 SF FL	4099854292859
	SENSOR SF FLAT LEADER FOLLOWER	4099854292897

EQUIPMENT / ACCESSORIES

- EVERLOOP luminaire: upgrades and replacements available
- Decorative silver frame separately available

DOWNLOAD DATA

Documents and certificates	Document name
 User Instruction	UI Surface Flat
 Addon Technical Information	LISO Insert SF FLAT
 Legal information	Legal Insert SF FLAT
 Certificates	ENEC SF FLAT
 Certificates	CEE Eligibility Attestation BAR-EQ-110 FR
 Certificates	CEE Eligibility Attestation BAT-EQ-127 FR


Photometric and lighting design files		Document name
	IES file (IES)	SF FLAT SQ SEN 330 P 19W 3000K 2490lm
	IES file (IES)	SF FLAT SQ SEN 330 P 19W 4000K 2660lm
	LDT file (Eulumdat)	SF FLAT SQ SEN 330 P 19W 3000K 2490lm
	LDT file (Eulumdat)	SF FLAT SQ SEN 330 P 19W 4000K 2660lm
	UGR file (UGR table)	SF FLAT SQ SEN 330 P 19W 3000K 2490lm
	UGR file (UGR table)	SF FLAT SQ SEN 330 P 19W 4000K 2660lm
	LDC typ cone	SF FLAT SQ SEN 330 P 19W 3000K 2490lm
	LDC typ cone	SF FLAT SQ SEN 330 P 19W 4000K 2660lm
	LDC typ polar	SF FLAT SQ SEN 330 P 19W 3000K 2490lm
	LDC typ polar	SF FLAT SQ SEN 330 P 19W 4000K 2660lm
CAD/BIM files		Document name
	CAD_STEP_3D	SF FLAT SQ 330

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854292712	Folding box 1	72 mm x 336 mm x 336 mm	1761.00 g	8.13 dm <sup>3</sup>
4099854292729	Shipping box 6	448 mm x 353 mm x 358 mm	11229.00 g	56.62 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.


ADDITIONAL CATALOG INFORMATION






SF FLAT SQ SEN 330	ORDER	CCT	W	h	h <sub>max</sub>	h <sub>min</sub>	h <sub>cut</sub>	h <sub>cut</sub>	h <sub>cut</sub>	h <sub>cut</sub>
SF FLAT SQ SEN 330	SR-UGR-3000K	4000K	19	336	336	-	-	-	-	-
SF FLAT SQ SEN 330	SR-UGR-4000K	3000K	19	336	336	-	-	-	-	-
SF FLAT SQ SEN 330	SR-UGR-3000K	4000K	27	336	336	-	-	-	-	-
SF FLAT SQ SEN 330	SR-UGR-4000K	3000K	27	336	336	-	-	-	-	-
SF FLAT SQ SEN 330	SR-UGR-3000K	4000K	27	353	358	0.0	0.0	0.0	0.0	0.0
SF FLAT SQ SEN 330	SR-UGR-4000K	3000K	27	353	358	0.0	0.0	0.0	0.0	0.0



www.ledvance.com/everloop-replacement





## References / Links

– For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.