

PRODUCT DATASHEET Neon Digital Flex IP44 5M RGB + RC

NEON DIGITAL FLEX | Decorative colorful LED Strips for outdoor use with homogeneous illumination



Areas of application

- Gardens, balconies and other outdoor areas
- Indirect and direct lighting
- Living areas

Product benefits

- Easy and quick installation

Product features

- Switch on and off, color changing and dimming via remote control
- Type of protection: IP44
- Dimmable



TECHNICAL DATA

Electrical data

| Nominal wattage | 23.00 W |
|------------------------|---------------------|
| Nominal voltage | 220240 V |
| Mains frequency | 5060 Hz |
| Nominal current | 170.000 mA |
| Power factor λ | > 0.50 |
| Protection class | II |
| Operating mode | External LED driver |

Photometrical data

| Luminous flux | 180 lm |
|---------------------------|--------|
| Luminous efficacy | 8 lm/W |
| Color temperature | RGB |
| Light color (designation) | RGB |
| Color rendering index Ra | > 80 |
| Beam angle | 160 ° |

Dimensions & Weight

| Length | 5000.00 mm |
|----------------|------------|
| Width | 6.70 mm |
| Height | 13.50 mm |
| Product weight | 632.00 g |



Materials & Colors

| Body material | Silicone |
|-----------------|--------------------|
| Cover material | Polycarbonate (PC) |
| Mercury content | 0.0 mg |

Application & Mounting

| Ambient temperature range | -20+40 °C |
|------------------------------|-----------------|
| Temperature range at storage | -20+80 °C |
| Type of connection | Plug, EU |
| Type of protection | IP44 |
| Dimmable | Yes |
| Mounting type | Surface |
| Mounting location | All surfaces |
| Application environment | Outdoor |
| LED module replaceable | Not replaceable |
| With light source | Yes |
| | |

Lifespan

| Lifespan L70/B50 at 25 °C | 30000 h ¹⁾ |
|----------------------------|-----------------------|
| Number of switching cycles | 15000 |

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

BATTERY

| Type of Battery | Li metal button cell battery |
|------------------------------|------------------------------|
| Battery size [GMS] | CR2025 |
| Number of included batteries | 1 |
| Nominal voltage of battery | 3 V |
| Nominal capacity of battery | 150 mAh |

Certificates & Standards

| Standards | CE / EAC |
|-----------|----------|
|-----------|----------|

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- Remote control and battery included

DOWNLOAD DATA

| | Documents and certificates | Document name |
|-----|----------------------------|------------------|
| POF | User Instruction | NEON DIGITALFLEX |

| | Documents and certificates | Document name |
|-----|----------------------------|---|
| POF | Declarations of conformity | NEON DIGITALFLEX 5M REMOTE RGB IP44LEDV |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075504769 | Folding box 1 | 64 mm x 299 mm x 275 mm | 914.00 g | 5.26 dm ³ |
| 4058075504776 | Shipping box 4 | 570 mm x 314 mm x 168 mm | 4305.00 g | 30.07 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.