

PRODUCT DATASHEET Indoor Garden Kit 450mm

Indoor Garden KIT 450 WT | LED Grow Light with two cultivation boxes



Areas of application

- Indoor Gardening
- Kitchens
- Living areas

Product benefits

- Specially developed LED spectrum promotes photosynthesis in most plants
- Imitates day/night cycle by automatic timer operation

Product features

- Uses a combination of white full-spectrum LEDs and red LEDs
- Height of lamp head adjustable according to height of the plant



TECHNICAL DATA

Electrical data

| Nominal wattage | 20.00 W |
|---|---------------|
| Nominal voltage | 220240 V |
| Mains frequency | 5060 Hz |
| Nominal current | 180.000 mA |
| Inrush current | 19.7 A |
| Max. number of luminaires per miniature circuit breaker B16 | 6 |
| Max. number of luminaires per miniature circuit breaker C10 | 7 |
| Max. number of luminaires per miniature circuit breaker C16 | 11 |
| Power factor λ | 0.50 |
| Protection class | П |
| Operating mode | Mains voltage |

Photometrical data

| Luminous flux | 1350 lm |
|--|---------------|
| Luminous efficacy | 67 lm/W |
| Color temperature | 3550 K |
| Light color (designation) | Neutral White |
| Color rendering index Ra | > 80 |
| Standard deviation of color matching | < 6 sdcm |
| Photobiological safety group acc. to EN62778 | RG1 |
| Photobiological safety group acc. to EN62471 | RG1 |
| Beam angle | 110° |

Dimensions & Weight

| Length | 189.00 mm |
|----------------|-----------|
| Width | 453.00 mm |
| Height | 476.00 mm |
| Product weight | 2200.00 g |

INDOOR GARDEN KIT 450 WT

Materials & Colors

| Product color | White |
|-----------------|-------------------------|
| Housing color | White |
| Body material | Plastic stainless steel |
| Cover material | Polycarbonate (PC) |
| Mercury content | 0.0 mg |

Application & Mounting

| Ambient temperature range | -20+40 °C |
|--|------------------|
| Temperature range at storage | -20+70 °C |
| Type of connection | Plug type C (EU) |
| Type of protection | IP20 |
| Protection class IK (shock resistance) | IK03 |
| Dimmable | No |
| Mounting type | Standing |
| Mounting location | All surfaces |
| Application environment | Indoor |
| Adjustable | Yes |
| LED module replaceable | Not replaceable |
| With light source | Yes |

Lifespan

| Lifespan L70/B50 at 25 °C | 25000 h ¹⁾ |
|----------------------------|-----------------------|
| Number of switching cycles | 15000 |

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Emergency lighting

| Luminous flux in maintained operation mode | - |
|--|---|
|--|---|

Certificates & Standards

| | | Standards | CE |
|--|--|-----------|----|
|--|--|-----------|----|

EQUIPMENT / ACCESSORIES

- Including cultivation boxes with water level indication

DOWNLOAD DATA

| | Documents and certificates | Document name | |
|----------------------------|----------------------------|-----------------------------|--|
| PDF User Instruction | | INDOOR GARDEN KIT | |
| Declarations of conformity | Declarations of conformity | EC_Indoor Garden KIT 450 WT | |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075576131 | Folding box | 197 mm x 487 mm x 142 mm | 2471.00 g | 13.62 dm ³ |
| 4058075576148 | Shipping box 4 | 508 mm x 418 mm x 331 mm | 10917.00 g | 70.29 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.