

# PRODUCT DATASHEET

## NIGHTLUX Hall Silver

NIGHTLUX® Hall | Mobile nightlights with motion sensor and tilt function, battery-powered



### Areas of application

- For a very large range of uses
- Indoor and outdoor
- Entrances / Hallways
- Corridors

### Product benefits

- Attractive and functional design
- Economical operation due to low power consumption
- Easy and fast mounting on nearly every surface (adhesive tape or screws)
- Light direction individually adjustable
- Accessories for flexible mounting options included

### Product features

- Integrated light and motion sensor
- Available in two housing colors
- Switch for Auto- or On/Off-Mode
- Type of protection: IP54



## TECHNICAL DATA

### Electrical data


Nominal wattage	0.25 W
Nominal voltage	4,5 V
Mains frequency	0 Hz
Nominal current	55.000 mA
Max. number of luminaires per miniature circuit breaker C10	-
Protection class	III
Operating mode	Battery

### Photometrical data

Luminous flux	14 lm
Luminous efficacy	4 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	≤6 sdc <sub>m</sub>

### Dimensions & Weight

Length	84.00 mm
Width	73.00 mm
Height	22.00 mm
Product weight	98.00 g



PG NIGHTLUX Hall MiPRC

### Materials & Colors

Product color	Silver
Housing color	Silver

Body material	Polycarbonate (PC)
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	0...+25 °C
Temperature range at storage	-20...+50 °C
Type of protection	IP54
Dimmable	No
Mounting type	Surface
Mounting location	Wall
Application environment	Indoor
LED module replaceable	Not replaceable
With light source	Yes

### Lifespan

Lifespan L70/B50 at 25 °C	25000 h <sup>1)</sup>
---------------------------	-----------------------

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Sensor

Type of sensor	Light / Motion
Sensor technology	Passive infrared (PIR)

### BATTERY

Type of Battery	Alkaline
Battery size [GMS]	AAA
Number of included batteries	3
Nominal voltage of battery	1.5 V


### Certificates & Standards

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No

### EQUIPMENT / ACCESSORIES

– Batteries included: 3x1.5 V LR03 (AAA)

### DOWNLOAD DATA

Documents and certificates	Document name
 Declarations of conformity	CE Declaration Nightlux Hall

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075260672	Blister 1	25 mm x 140 mm x 195 mm	118.00 g	0.68 dm <sup>3</sup>
4058075260689	Shipping box 6	163 mm x 154 mm x 210 mm	817.00 g	5.27 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.