

PRODUCT DATASHEET

LED WORKLIGHT VALUE BATTERY FLEX 7W 865

WORKLIGHTS VALUE BATTERY | Mobile battery powered worklight in value class



Areas of application

- Renovation
- Garages
- Workshops
- Basement

Product benefits

- USB-Charging function from integrated power bank feature
- Independent of power supply due to battery technology

Product features

- Worklight with swiveling head
- Battery powered, portable worklight
- Battery rechargeable via USB cable



TECHNICAL DATA

Electrical data


Nominal wattage	14.00 W
Nominal voltage	5 V
Nominal current	1000.000 mA
Power factor λ	1.00
Protection class	III
Operating mode	Battery

Photometrical data

Luminous flux	1400 lm
Luminous efficacy	100 lm/W
Color temperature	6500 K
Light color (designation)	Cool Daylight
Color rendering index Ra	≥ 80
Standard deviation of color matching	< 6 sdc _m
Luminous intensity	600 cd
Flickering metric (Pst LM)	< 1
Stroboscope effect metric (SVM)	< 0.9
Photobiological safety group acc. to EN62778	RG1
Beam angle	110 °

Dimensions & Weight

Length	200.00 mm
Width	59.00 mm
Height	141.00 mm
Product weight	600.00 g



LED WORKLIGHT VAL BAT FLEX
2X10W 865

Materials & Colors

Product color	Black/Gray
Housing color	Black/Gray
Body material	Plastic
Cover material	Plastic
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-10...+40 °C
Temperature range at storage	-20...+60 °C
Type of connection	USB
Type of protection	IP20
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Standing
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Number of switching cycles	7500
----------------------------	------

BATTERY

Battery size [GMS]	Others
--------------------	--------

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No





Additional product data

Product remark	Available from November 2023
Number of illuminants	2

EQUIPMENT / ACCESSORIES

– 60cm USB-C charging cable

DOWNLOAD DATA

Documents and certificates	Document name
 User Instruction	LED WORKLIGHT VAL BAT FLEX
 Legal information	Legal insert SMART OUTD ENDURA SOLAR WORKLIGHT BAT
 Declarations of conformity	LED WORKLIGHT VAL BAT
 Declarations Of Conformity UKCA	LED WORKLIGHT VAL BAT

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075834026	Folding box 1	67 mm x 212 mm x 147 mm	674.00 g	2.09 dm ³
4058075834033	Shipping box 8	285 mm x 230 mm x 320 mm	5881.00 g	20.98 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.