

# PRODUCT DATASHEET

## LED WORKLIGHT VALUE BATTERY POCKET 10W 865

WORKLIGHTS VALUE BATTERY | Mobile battery powered worklight in value class



### Areas of application

- Renovation
- Garages
- Workshops
- Basement

### Product benefits

- USB-Charging function from integrated power bank feature
- Independent of power supply due to battery technology

### Product features

- Worklight with swiveling head
- Battery powered, portable worklight
- Battery rechargeable via USB cable



## TECHNICAL DATA

### Electrical data


Nominal wattage	10.00 W
Nominal voltage	5 V
Nominal current	1000.000 mA
Power factor $\lambda$	1.00
Protection class	III
Operating mode	Battery

### Photometrical data

Luminous flux	800 lm
Luminous efficacy	80 lm/W
Color temperature	6500 K
Light color (designation)	Cool Daylight
Color rendering index Ra	$\geq 80$
Standard deviation of color matching	$< 6$ sdc <sub>m</sub>
Luminous intensity	350 cd
Flickering metric (Pst LM)	$< 1$
Stroboscope effect metric (SVM)	$< 0.9$
Photobiological safety group acc. to EN62778	RG1
Beam angle	100 °

### Dimensions & Weight

Length	100.00 mm
Width	45.00 mm
Height	100.00 mm
Product weight	250.00 g



LED WORKLIGHT VAL BAT  
POCKET 10W 865

### Materials & Colors

Product color	Black/Gray
Housing color	Black/Gray
Body material	Plastic
Cover material	Plastic
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	-10...+40 °C
Temperature range at storage	-20...+60 °C
Type of connection	USB
Type of protection	IP54
Protection class IK (shock resistance)	IK06
Dimmable	Yes
Type of dimming	3 DIM
Mounting type	Standing
LED module replaceable	Not replaceable
With light source	Yes

### Lifespan

Number of switching cycles	7500
----------------------------	------

### BATTERY

Battery size [GMS]	ICR18650
--------------------	----------

### Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No





### Additional product data

Product remark	Available from November 2023
Number of illuminants	1

### EQUIPMENT / ACCESSORIES

– 60cm USB-C charging cable

### DOWNLOAD DATA

Documents and certificates	Document name
 User Instruction	LED WORKLIGHT VAL BAT POCKET
 Legal information	Legal insert SMART OUTD ENDURA SOLAR WORKLIGHT BAT
 Declarations of conformity	LED WORKLIGHT VAL BAT
 Declarations Of Conformity UKCA	LED WORKLIGHT VAL BAT

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075831117	Folding box 1	56 mm x 106 mm x 118 mm	278.00 g	0.70 dm <sup>3</sup>
4058075831124	Shipping box 8	248 mm x 228 mm x 143 mm	2451.00 g	8.09 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.