

PRODUCT DATASHEET

Cabinet LED Panel Sensor 300x200mm Two Light

Cabinet LED Panel | Low voltage undercabinet luminaires with rectangular shape

Areas of application

- Shelf and undercabinet lighting



Product benefits

- Low voltage luminaire for DC operation with external driver
- Very slim design
- Homogenous light distribution
- Easy and fast mounting on nearly every surface (adhesive tape or screws)

Product features

- Luminous flux: up to 450 lm
- Switch on and off by movements with 5 cm distance in front of the infrared motion sensor
- Stepless dimming by covering the infrared motion sensor in 5 cm distance for at least one second



- Material: aluminum
- Product color: white
- Available as single and double luminaire kit

TECHNICAL DATA

Electrical data


| | |
|---|---------------------|
| Nominal wattage | 14.00 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Nominal current | 140.000 mA |
| Max. number of luminaires per miniature circuit breaker C10 | - |
| Power factor λ | > 0.5 |
| Protection class | II |
| Operating mode | External LED driver |

Photometrical data

| | |
|--|---------------------------|
| Luminous flux | 900 lm |
| Total luminous flux of contained light sources | 960 lm |
| Luminous efficacy | 64 lm/W |
| Color temperature | 3000 K |
| Light color (designation) | Warm White |
| Color rendering index Ra | ≥ 80 |
| Standard deviation of color matching | ≤ 6 sdc _m |
| Photobiological safety group acc. to EN62778 | RG1 |
| Photobiological safety group acc. to EN62471 | RG0 |
| Beam angle | 110 ° |

Dimensions & Weight

| | |
|----------------|-----------|
| Length | 300.00 mm |
| Width | 200.00 mm |
| Height | 8.00 mm |
| Product weight | 1076.00 g |
| Cable length | 1500 mm |



Cabinet LED Panel 30x20

Materials & Colors

| | |
|-----------------|---------------------------------------|
| Product color | White |
| Housing color | White |
| Body material | Acrylonitrile butadiene styrene (ABS) |
| Cover material | Polycarbonate (PC) |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|--|--------------------|
| Ambient temperature range | -20...+40 °C |
| Temperature range at storage | -30...+70 °C |
| Type of connection | Plug type C (EU) |
| Type of protection | IP20 |
| Protection class IK (shock resistance) | IK03 |
| Dimmable | Yes |
| Mounting type | Surface |
| Mounting location | Cabinet undersides |
| Application environment | Indoor |
| LED module replaceable | Not replaceable |
| With light source | Yes |

Lifespan

| | |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C | 30000 h ¹⁾ |
| Number of switching cycles | 100000 |

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Sensor

| | |
|----------------------------------|--------------------|
| Type of sensor | Motion |
| Sensor technology | Infrared/Photocell |
| Detection range of motion sensor | 5 cm |




Certificates & Standards

| | |
|--|----------|
| Standards | CE / EAC |
| Luminaire with limited surface temperature, "D sign" | No |

EQUIPMENT / ACCESSORIES

– External mains adapter (cable length: 1.5 m) included

DOWNLOAD DATA

| Documents and certificates | Document name |
|---|-----------------------------|
|  User Instruction | CABINET LED PANEL |
|  Legal information | Legal insert B-not dimmable |
|  Declarations of conformity | CE Declaration Cabinet LED |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075268340 | Folding box 1 | 38 mm x 204 mm x 400 mm | 1164.00 g | 3.10 dm ³ |
| 4058075268357 | Shipping box 8 | 450 mm x 392 mm x 171 mm | 9851.00 g | 30.16 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.