

PRODUCT DATASHEET

Decor Spot Venus Black 4 Spot

DECOR SPOT VENUS BLACK | Ceiling mounted luminaires with adjustable spotlights



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Kitchens, workspaces
- Ceiling and wall surface mounting

Product benefits

- High-quality housing with matt white or matt black surface
- Easy mounting

Product features

- Luminaire family features four versions with up to 4 spot heads
- On/off switch on 1-head version for easy operation
- Adjustable heads



TECHNICAL DATA

Electrical data


Nominal wattage	21.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	150.000 mA
Inrush current	1.025 A
Inrush current time T_{h50}	260 μ s
Max. number of luminaires per miniature circuit breaker B16	85
Max. number of luminaires per miniature circuit breaker C16	85
Power factor λ	> 0.5
Total harmonic distortion	< 70 %
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	910 lm
Total luminous flux of contained light sources	2000 lm
Luminous efficacy	43 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	80
Standard deviation of color matching	6 sdc _m
Luminous intensity	400 cd
Flickering metric (Pst LM)	<10 %
Stroboscope effect metric (SVM)	≤0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	95 °

Dimensions & Weight

Length	695.00 mm
Width	100.00 mm
Height	105.00 mm
Product weight	1460.00 g



DECOR SPOT VENUS 695MM 21W
830

Materials & Colors

Product color	Black
Housing color	Black
Body material	Steel
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+40 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Adjustable	Yes
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	15000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No





Additional product data

Product remark	Available from February 2024
----------------	------------------------------

EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

DOWNLOAD DATA

Documents and certificates	Document name
 User Instruction	Decor Spot Venus
 Legal information	Decor Spot lights
 Declarations of conformity	CE Declaration Decor Spot Pluto
 Declarations Of Conformity UKCA	UKCA Declaration DECOR SPOT

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075833692	Folding box 1	132 mm x 142 mm x 743 mm	1692.00 g	13.93 dm ³
4058075833708	Shipping box 4	758 mm x 298 mm x 289 mm	7656.00 g	65.28 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.