

PRODUCT DATASHEET

Decor Spot Saturn CLICK-CCT Black 3 Spot

DECOR SPOT SATURN BLACK | Ceiling mounted luminaires with adjustable spotlights featuring selectable light color temperatures via wall switch



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Kitchens, workspaces
- Ceiling and wall surface mounting

Product benefits

- High-quality housing with matt white or matt black surface
- Easy mounting

Product features

- Luminaire family features four versions with up to 3 spot heads
- Click-CCT version: color temperature adjustable in three steps by repeated switching
- On/off switch on 1-head version for easy operation
- Adjustable heads



TECHNICAL DATA

Electrical data

Nominal wattage	29.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	126.000 mA
Inrush current	2.877 A
Inrush current time T_{h50}	570 μ s
Max. number of luminaires per miniature circuit breaker B16	50
Max. number of luminaires per miniature circuit breaker C16	86
Power factor λ	> 0.90
Total harmonic distortion	< 70 %
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	690 lm
Total luminous flux of contained light sources	3270 lm
Luminous efficacy	29 lm/W
Color temperature	3000 K / 4200 K / 6500 K
Reference control setting of contained light source (Kelvin)	3000 K
Light color (designation)	Warm White / Cool White / Cool Daylight
Color rendering index Ra	80
Standard deviation of color matching	6 sdc _m
Luminous intensity	Not relevant
Flickering metric (Pst LM)	<10%
Stroboscope effect metric (SVM)	≤0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	118 °

Dimensions & Weight

Length	665.00 mm
Width	75.00 mm
Height	147.00 mm
Product weight	1300.00 g



DECOR SPOT SATURN W 668MM
30W CCT

Materials & Colors

Product color	Black
Housing color	Black
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+40 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Adjustable	Yes
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	15000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No

Additional product data





Product remark

Available from February 2024

EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

DOWNLOAD DATA

Documents and certificates		Document name
	User Instruction	Decor Spot Saturn CLICK-CCT
	Legal information	Decor Spot lights
	Declarations of conformity	CE Declaration Decor Spot Pluto
	Declarations Of Conformity UKCA	UKCA Declaration DECOR SPOT

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075833517	Folding box 1	117 mm x 182 mm x 743 mm	1548.00 g	15.82 dm ³
4058075833524	Shipping box 4	757 mm x 378 mm x 259 mm	7330.00 g	74.11 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.