

PRODUCT DATASHEET

LED Spot G9 4 x 1.9W 2700K

LED SPOT G9 | Ceiling mounted luminaires with adjustable G9 spotlights



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Kitchens, workspaces
- Ceiling and wall surface mounting

Product benefits

- Energy savings of up to 90 % compared to halogen lamp spotlights
- Timeless design
- Flexible thanks to replaceable LED lamps
- Easy mounting

Product features

- Luminaire family features five versions with up to 6 spot heads
- Housing surface made of brushed nickel
- Diffuser made of frosted glass
- Adjustable head



TECHNICAL DATA

Electrical data

Nominal wattage	7.60 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	64.000 mA
Inrush current	15.36 A
Max. number of luminaires per miniature circuit breaker B16	10
Max. number of luminaires per miniature circuit breaker C10	10
Max. number of luminaires per miniature circuit breaker C16	16
Power factor λ	> 0.4
Protection class	I
Operating mode	Mains voltage

Photometrical data

Luminous flux	800 lm
Total luminous flux of contained light sources	920 lm
Luminous efficacy	105 lm/W
Color temperature	2700 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	≤6 sdcn
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	300 °

Dimensions & Weight

Length	646.00 mm
Width	90.00 mm
Height	165.00 mm
Product weight	730.00 g

LED SPOT G9 4X1,9W 827

Materials & Colors

Product color	Silver
Housing color	Silver
Body material	Aluminum
Cover material	Glass
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screw terminal
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Indoor
Adjustable	Yes
With light source	Yes
Holder designation	G9

Lifespan

Lifespan L70/B50 at 25 °C	15000 h ¹⁾
Number of switching cycles	10000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No

Additional product data




Product remark	Maximum bulb wattage: 40 W
Number of illuminants	4

EQUIPMENT / ACCESSORIES

– Equipped with OSRAM LED LAMP EAN 4058075432307

– Complete mounting and connecting accessories included

DOWNLOAD DATA

Documents and certificates		Document name
	User Instruction	LED SPOT G9
	Declarations of conformity	LED SPOT GU10 G9
	Declarations Of Conformity UKCA	Fixed LUM

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075540682	Folding box 1	140 mm x 120 mm x 670 mm	958.00 g	11.26 dm ³
4058075540699	Shipping box 4	680 mm x 255 mm x 300 mm	5162.00 g	52.02 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.