

# PRODUCT DATASHEET ENDURA Classic Calice Wall Sensor E27

ENDURA CLASSIC CALICE | Stainless steel luminaires with glass diffuser



## Areas of application

- Building facades
- Entrance lighting
- Patios, balconies
- Pathway lighting
- Driveways

## **Product benefits**

- High flexibility in the choice of the light source thanks to E27 socket
- Easy and quick installation

#### **Product features**

- Available with and without motion sensor
- Stainless steel housing
- Type of protection: IP44



## **TECHNICAL DATA**

## Electrical data


Nominal voltage	220240 V
Mains frequency	5060 Hz
Power factor $\lambda$	> 0.50
Protection class	1
Operating mode	Mains voltage

# Photometrical data

Standard deviation of color matching	< 6 sdcm
--------------------------------------	----------

## **Dimensions & Weight**

Length	161.00 mm
Width	120.00 mm
Height	305.00 mm
Product weight	950.00 g



## Materials & Colors

Product color	Steel
Housing color	Steel
Body material	Stainless steel
Cover material	Glass
Mercury content	0.0 mg

# Application & Mounting

Type of connection	Terminal, 3-Pole (L, N, PE)	
Type of protection	IP44	
Dimmable	No	
Mounting type	Surface	
Mounting location	Wall	
Application environment	Outdoor	
With light source	No	

#### Sensor

Type of sensor	Light / Motion	
Sensor technology	Passive infrared (PIR)	
Sensor detection angle	90 °	
Sensor controlled switching time	5 s6 min	
Detection range of motion sensor	58 m	
Detection threshold of daylight sensor	030 lx	

# **Certificates & Standards**

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No

# Additional product data

Product remark

Maximum bulb wattage: 60 W

## EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- No light sources included

# DOWNLOAD DATA

	Documents and certificates	Document name	
POF	User Instruction	ENDURA CLASSIC CALICE	
POF	Legal information	Legal insert I-Outdoor	
POF	Declarations of conformity	ENDURA CLASSIC CALICE WALL S	

Documents and certificates	Document name

POF

Declarations Of Conformity UKCA

CLASSIC CALICE WALL

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075477971	Folding box 1	202 mm x 162 mm x 349 mm	1109.00 g	11.42 dm <sup>3</sup>
4058075477988	Shipping box 4	420 mm x 365 mm x 340 mm	5230.00 g	52.12 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.