

PRODUCT DATASHEET ENDURA Classic Calice Wall E27

ENDURA CLASSIC CALICE | Stainless steel luminaires with glass diffuser



Areas of application

- Building facades
- Entrance lighting
- Patios, balconies
- Pathway lighting
- Driveways

Product benefits

- High flexibility in the choice of the light source thanks to E27 socket
- Easy and quick installation

Product features

- Available with and without motion sensor
- Stainless steel housing
- Type of protection: IP44



TECHNICAL DATA

Electrical data


Nominal voltage	220240 V
Mains frequency	5060 Hz
Power factor λ	> 0.50
Protection class	T. Control of the con
Operating mode	Mains voltage

Photometrical data

Standard deviation of color matching	< 6 sdcm
--------------------------------------	----------

Dimensions & Weight

Length	161.00 mm
Width	120.00 mm
Height	290.00 mm
Product weight	900.00 g



Materials & Colors

Product color	Steel
Housing color	Steel
Body material	Stainless steel
Cover material	Glass
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C

Type of connection	Terminal, 3-Pole (L, N, PE)	
Type of protection	IP44	
Dimmable	No	
Mounting type	Surface	
Mounting location	Wall	
Application environment	Outdoor	
With light source	No	

Certificates & Standards

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No

Additional product data

Product remark Maximum bulb wattage: 60 W
--

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- No light sources included

DOWNLOAD DATA

	Documents and certificates	Document name	
POF	User Instruction	ENDURA CLASSIC CALICE	
POF	Legal information	Legal insert I-Outdoor	
POF	Declarations of conformity	ENDURA CLASSIC CALICE WALL E27 ST	
POF	Declarations Of Conformity UKCA	Fixed LUM without EMC	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075477957	Folding box 1	202 mm x 162 mm x 334 mm	1055.00 g	10.93 dm ³
4058075477964	Shipping box 4	420 mm x 350 mm x 340 mm	4997.00 g	49.98 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.