

# PRODUCT DATASHEET ENDURA Classic Post Up E27

ENDURA® CLASSIC POST | Stainless steel luminaires with glass diffuser



### Areas of application

- Outdoor use (IP44)
- Building facades
- Entrance lighting
- Patios, balconies
- Pathway lighting
- Driveways

### Product benefits

- High flexibility in the choice of the light source thanks to E27 socket
- Suitable for smart applications thanks to compatibility with Smart + lamps from LEDVANCE
- Easy and quick installation

### Product features

- Stainless steel housing
- Diffuser made of clear glass with hammer finish
- Available with and without motion sensor
- Available as wall and bollard luminaires




# **TECHNICAL DATA**

# Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	T .
Operating mode	Mains voltage

# Dimensions & Weight

Diameter	127.0 mm
Length	212.00 mm
Width	127.00 mm
Height	193.00 mm
Product weight	1065.00 g



# Materials & Colors

Product color	Steel
Housing color	Steel
Body material	Stainless steel
Mercury content	0.0 mg

# Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+85 °C
Type of connection	Screw terminal
Type of protection	IP44
Dimmable	No
Mounting type	Surface

Mounting location	Wall
Application environment	Outdoor
With light source	No
Holder designation	E27

# Certificates & Standards

# Additional product data

Product remark	Maximum bulb wattage: 60 W
Number of illuminants	1

# **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included
- No light sources included

# DOWNLOAD DATA

	Documents and certificates	Document name
POF	User Instruction	ENDURA CLASSIC POST
PDF	Legal information	Legal insert I-Outdoor
PDF	Declarations of conformity	CE Declaration Endura Classic Post

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075206502	Folding box 1	141 mm x 239 mm x 242 mm	1291.00 g	8.16 dm <sup>3</sup>
4058075206519	Shipping box 4	500 mm x 257 mm x 300 mm	5814.00 g	38.55 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.