

# PRODUCT DATASHEET

## Orbis Click-CCT 310mm 14W

ORBIS® CCT / DIM | LED luminaire with CCT function via wall switch or remote control with CCT and dimming



### Areas of application

- For indoor use only
- Decorative domestic lighting
- Ceiling and wall surface mounting

### Product benefits

- Very homogenous light
- Easy and quick installation

### Product features

- Ceiling luminaire with advanced LED technology
- Circular light emission
- Remote-CCT version: color temperature, dimming, timer, memory and night functions via remote control
- Click-CCT version: color temperature adjustable in three steps by repeated switching



## TECHNICAL DATA

### Electrical data

Nominal wattage	15.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	68 mA
Inrush current	2.22 A
Max. number of luminaires per miniature circuit breaker B16	93
Max. number of luminaires per miniature circuit breaker C10	90
Max. number of luminaires per miniature circuit breaker C16	144
Power factor $\lambda$	> 0.90
Protection class	I
Operating mode	External LED driver

### Photometrical data

Luminous flux	1000 lm
Total luminous flux of contained light sources	1700 lm
Luminous efficacy	67 lm/W
Color temperature	2700 K / 4000 K / 6500 K
Light color (designation)	Warm White / Cool White / Cool Daylight
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG0
Beam angle	120 °

### Dimensions & Weight

Diameter	310 mm
Height	80.00 mm
Product weight	540.00 g

### Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Polycarbonate (PC)

Mercury content	0.0 mg
-----------------	--------

### Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+70 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
LED module replaceable	Not replaceable
With light source	Yes

### Lifespan

Lifespan L70/B50 at 25 °C	25000 h <sup>1)</sup>
Number of switching cycles	12500

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Emergency lighting

Type of emergency light operation	Non-maintained
Luminous flux in maintained operation mode	-
Luminous flux in emergency operation mode	-



### Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No

### EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

### DOWNLOAD DATA

Documents and certificates	Document name
 User Instruction	ORBIS 3100 410 CCT
 Declarations of conformity	ORBIS 410MM 24W 827-865 CLICK-CCT LEDV

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075651739	Folding box 1	338 mm x 103 mm x 338 mm	720.00 g	11.77 dm <sup>3</sup>
4058075651746	Shipping box 5	542 mm x 357 mm x 369 mm	4580.00 g	71.40 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.