

PRODUCT DATASHEET

Orbis Frame Click Sensor 335mm 24W

ORBIS CLICK SENSOR | C



Areas of application

- Corridors, entrance areas

Product benefits

- Easy and quick installation

Product features

- Luminaires activated by sensor mode or conventional wall switch
- Operating mode easily changed by three clicks of wall switch
- Motion sensor (microwave technology) with adjustable detection parameters



TECHNICAL DATA

Electrical data


Nominal wattage	24.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor λ	> 0.70
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	1320 lm
Total luminous flux of contained light sources	2900 lm
Luminous efficacy	55 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcn
Beam angle	120 °

Dimensions & Weight

Diameter	335.00 mm
Height	75.00 mm
Product weight	593.00 g



ORBIS FRAME 335 RD 24W 830
CLICKSEN

Materials & Colors

Product color	White
Housing color	White
Body material	Steel
Cover material	Polymethylmethacrylate (PMMA)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...40 °C
Type of connection	Push button terminal, 2-pole
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	15000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Sensor

Type of sensor	Light / Motion
Sensor technology	Microwave
Sensor detection angle	120 °
Sensor controlled switching time	5 s...30 min
Detection range of motion sensor	2...6 m
Detection threshold of daylight sensor	2...50 lx





Certificates & Standards

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No

EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

DOWNLOAD DATA

Documents and certificates		Document name
	User Instruction	ORBIS
	Legal information	Legal insert
	Declarations of conformity	ORBIS CLICK SEN
	Declarations Of Conformity UKCA	ORBIS CLICKSEN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075472792	Folding box 1	362 mm x 82 mm x 367 mm	834.00 g	10.89 dm ³
4058075472808	Shipping box 5	432 mm x 377 mm x 390 mm	5150.00 g	63.52 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.