

PRODUCT DATASHEET

NAV 100 LED FILAMENT AMBER V 3200LM 30W 718 E40

NAV LED FILAMENT AMBER V | LED replacement for NAV lamps in design-oriented outdoor applications with reduced percentage of blue light



Areas of application

- Street and outdoor lighting
- Areas close to nature
- Residential areas
- Parks
- Historic buildings and districts
- Outdoor applications only in suitable luminaires

Product benefits

- Support wildlife protection thanks to very low percentage of blue light
- Support reduction of circadian disruption and improve the residents' life quality
- Better color rendering and enhanced visibility compared to traditional sodium vapor lamps (NAV)
- Same design as traditional NAV lamps with clear, tubular full glass bulb
- Full use of reflector of existing luminaire thanks to 360 degree beam angle
- Saves up to 70 % energy when used as replacement for sodium vapor lamps (NAV)
- Instant 100 % light, no warm-up time
- Similar light distribution as traditional NAV lamps

Product features

- Less than 1,5% of blue light (<500nm)
- Very warm light color of 1800K similar to traditional sodium vapor lamps (NAV)



- Suitable for operation with conventional control gear (CCG) or 230 V AC mains
- Power factor: 0.9
- Type of protection: IP65
- Surge protection: up to 2 kV (L-N)

TECHNICAL DATA

Electrical data

Nominal wattage	30 W
Construction wattage	30.00 W
Nominal voltage	220...240 V
Operating mode	CCG, AC Mains
Claimed equiv. conventional lamp power	100 W
Nominal current	125 mA
Type of current	AC
Inrush current	9.7 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	8
Max. lamp number on MCB B10 A - CCG without compensation	9
Max. lamp number on MCB B10 A - CCG with compensation	3
Max. lamp number on MCB B16 A	12
Max. lamp number on MCB B16 A - CCG without compensation	15
Max. lamp number on MCB B16 A - CCG with compensation	6
Total harmonic distortion	30 %
Power factor λ	> 0.90
Surge capability (L-N)	2 kV

Photometrical data

Luminous flux	3200 lm
Nominal useful luminous flux 90°	3200 lm
Luminous efficacy	106 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Amber
Color temperature	1800 K
Color rendering index Ra	70
Light color	718
Standard deviation of color matching	≤6 sdc _m
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	1
Stroboscope effect metric (SVM)	0,4

Light technical data

Beam angle	360 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	225.00 mm
Diameter	46.00 mm
Maximum diameter	46 mm
Product weight	170.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
Maximum temperature at tc test point	115 °C

Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	E40
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	Available from July 2024

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Energy consumption	30.00 kWh/1000h
--------------------	-----------------

Type of protection	IP65
Standards	CE / UKCA / EAC
Photobiological safety group acc. to EN62778	RG1

Country-specific categorizations

Order reference	NAV100 LED FIL
-----------------	----------------

LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------







Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E40
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Claim of equivalent power	No
Length	225.00 mm
Height	46.00 mm
Width	46.00 mm
Chromaticity coordinate x	0.549
Chromaticity coordinate y	0.408
R9 Colour rendering index	0.00
Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	0.9
LED light source replaces a fluorescent light source	No

Safety advice

- Not suitable for operation with ignitors
- Operation on the capacitor can lead to a reduction of the power factor of the system.
- When installed horizontally, the t_c point of the lamp is located on the top side of the lamp.
- Use in tight luminaires and luminaires with tight reflectors not recommended.
- Only suitable for temperatures of up to 50°C inside of the luminaire. Use in tight luminaires and luminaires with tight reflectors not recommended.

DOWNLOAD DATA

Documents and certificates		Document name
	User Instruction	NAV LED FILAMENT V
	Declarations of conformity	
Photometric and lighting design files		Document name
	IES file (IES)	NAV 100 LED FIL V 3200LM 30W 718 E40
	LDT file (Eulumdat)	NAV 100 LED FIL V 3200LM 30W 718 E40
	UGR file (UGR table)	NAV 100 LED FIL V 3200LM 30W 718 E40
	LDC typ polar	NAV 100 LED FIL V 3200LM 30W 718 E40

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075843622	Folding box 1	52 mm x 52 mm x 311 mm	241.00 g	0.84 dm ³
4058075843639	Shipping box 6	235 mm x 180 mm x 340 mm	1893.00 g	14.38 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.