

## PRODUCT DATASHEET

# HQI HIGHBAY 400 120 ° 140 W/4000 K E40

HQI LED HIGHBAY | LED replacement for HID lamps for high-bay luminaires



### Areas of application

- LED alternative for applications requiring a high luminous flux
- Industrial and storage facilities
- Outdoor applications only in suitable luminaires

### Product benefits

- Direct replacement for traditional HQI and NAV lamps thanks to CCG and ignitor compatibility
- Energy savings of up to 68 % when replacing traditional HQI lamps
- Effective thermal management for wide operating temperature range
- Low maintenance costs thanks to long lifetime
- Instant 100 % light, no warm-up time

### Product features

- Type of protection: IP40
- High surge protection: up to 4 kV (L-N)



## TECHNICAL DATA

### Electrical data

Nominal wattage	140 W
Construction wattage	140.00 W
Nominal voltage	110 V
Operating mode	Conventional control gear (CCG), Conventional control gear (CCG) and ignitor
Claimed equiv. conventional lamp power	400 W
Nominal current	3.6 A
Type of current	AC
Inrush current	50 A
Operating frequency	50 Hz
Mains frequency	50 Hz
Max. lamp number on MCB B10 A	11
Max. lamp number on MCB B16 A	18
Total harmonic distortion	< 80 %
Power factor $\lambda$	0.70

### Photometrical data

Luminous flux	20000 lm
Nominal useful luminous flux 90°	20000 lm
Luminous efficacy	142 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Standard deviation of color matching	≤6 sdc <sub>m</sub>
Rated LLMF at 6,000 h	0.80




EPREL data spectral diagram PROF LEDr 4000K

Light technical data

Beam angle	120 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	310.00 mm
Diameter	230.00 mm
Maximum diameter	230 mm
Product weight	1150.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
Maximum temperature at tc test point	75 °C

Lifespan

Lifespan L70/B50 at 25 °C	50000 h
Number of switching cycles	100000

Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

### Additional product data

Base (standard designation)	E40
Mercury content	0.0 mg

### Capabilities

Dimmable	No
----------	----

### Certificates & Standards

Energy efficiency class	E
Energy consumption	154.00 kWh/1000h
Type of protection	IP40
Standards	CE
Photobiological safety group acc. to EN62778	RG1

### Country-specific categorizations

Order reference	HQILEDH20000 14
-----------------	-----------------

### Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	E40
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	310.00 mm
Height	230.00 mm
Width	230.00 mm
Chromaticity coordinate x	0.381
Chromaticity coordinate y	0.379

Beam angle correspondence	SPHERE_360
Survival factor	0.90
Displacement factor	0.70
LED light source replaces a fluorescent light source	No
EPREL ID	567216
Model number	AC35216


**EQUIPMENT / ACCESSORIES**


- Safety sling for lamp included

**Safety advice**

- The bulb may be larger and heavier than the replaced bulb. Before installation it must be checked, if the luminaire and especially the holder is capable of carrying the weight of the lamp.
- Safety sling has to be installed.
- To ensure full light efficiency and product lifetime, it is recommended to detach any glass or cover of the luminaire.
- Only suitable for temperatures of up to 50°C inside of the luminaire.
- Not suitable for operation with 230 V line voltage or electronic control gear.

**DOWNLOAD DATA**

Documents and certificates		Document name
	User Instruction	HQI LED Highbay

Photometric and lighting design files		Document name
	Spectral power distribution	EPREL data spectral diagram PROF LEDr 4000K

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075612655	Folding box 1	247 mm x 247 mm x 333 mm	1371.00 g	20.32 dm <sup>3</sup>
4058075612662	Shipping box 4	515 mm x 515 mm x 355 mm	6161.00 g	94.15 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.