

PRODUCT DATASHEET

HQL LED FILAMENT V 6000LM 38W 840 E27

HQL LED FILAMENT V | LED replacement for HQL lamps in design-oriented outdoor applications



VALUE
CLASS

Areas of application

- Streets
- Area lighting
- Pedestrian zones
- Parks
- Outdoor applications only in suitable luminaires

Product benefits

- Same design as traditional HQL lamps with frosted, ellipsoid full glass bulb
- Full use of reflector of existing luminaire thanks to 360 degree beam angle
- Saves up to 78 % energy when used as replacement for mercury vapor lamps (HQL)
- Instant 100 % light, no warm-up time

Product features

- Replacement for HQL: Suitable for operation with conventional control gear (CCG) for HQL or 230 V mains
- Replacement for other HID: Suitable for operation with line voltage without control gear
- Power factor: 0.9
- Type of protection: IP65
- Surge protection: up to 2 kV (L-N)



TECHNICAL DATA


Electrical data

Nominal wattage	38 W
Construction wattage	38.00 W
Nominal voltage	220...240 V
Operating mode	CCG, AC Mains
Claimed equiv. conventional lamp power	125 W
Nominal current	160 mA
Type of current	AC
Inrush current	7.3 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	7
Max. lamp number on MCB B10 A - CCG without compensation	11
Max. lamp number on MCB B10 A - CCG with compensation	3
Max. lamp number on MCB B16 A	11
Max. lamp number on MCB B16 A - CCG without compensation	17
Max. lamp number on MCB B16 A - CCG with compensation	5
Total harmonic distortion	10 %
Power factor λ	> 0.90
Surge capability (L-N)	2 kV

Photometrical data

Luminous intensity	Not relevant
Luminous flux	6000 lm
Nominal useful luminous flux 90°	6000 lm
Luminous efficacy	157 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	80
Light color	840
Standard deviation of color matching	≤6 sdcn
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	1

Stroboscope effect metric (SVM)	0,4
---------------------------------	-----



EPREL data spectral diagram PROF
LEDr 4000K

Light technical data

Beam angle	360 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	217.00 mm
Diameter	90.00 mm
Maximum diameter	90 mm
Product weight	210.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
Maximum temperature at tc test point	80 °C

Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Energy efficiency class	D ¹⁾
Energy consumption	38.00 kWh/1000h
Type of protection	IP65
Standards	CE / EAC / UKCA
Photobiological safety group acc. to EN62778	RG1

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

Order reference	HQL LED FIL V 6
-----------------	-----------------

LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

Energy labelling regulation data acc EU 2019/2015









Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	217.00 mm
Height	90.00 mm
Width	90.00 mm

Chromaticity coordinate x	0,38
Chromaticity coordinate y	0,38
R9 Colour rendering index	0.00
Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	0.9
LED light source replaces a fluorescent light source	No
EPREL ID	1371169
Model number	AC46355,AC46355

Safety advice

- Not suitable for operation with ignitors
- Operation on the capacitor can lead to a reduction of the power factor of the system.
- When installed horizontally, the t_c point of the lamp is located on the top side of the lamp.
- Use in tight luminaires and luminaires with tight reflectors not recommended.
- Only suitable for temperatures of up to 50°C inside of the luminaire. Use in tight luminaires and luminaires with tight reflectors not recommended.

DOWNLOAD DATA

Documents and certificates		Document name
	User Instruction	HQL LED FILAMENT V
	Declarations of conformity	HID LED FILAMENT
	Declarations Of Conformity UKCA	HID LED FILAMENT
Photometric and lighting design files		Document name
	IES file (IES)	HQL LED FIL V 5400LM 38W 827 E40 LEDV
	LDT file (Eulumdat)	HQL LED FIL V 5400LM 38W 827 E40 LEDV
	UGR file (UGR table)	HQL LED FIL V 5400LM 38W 827 E40 LEDV
	LDC typ polar	HQL LED FIL V 5400LM 38W 827 E40 LEDV
	Spectral power distribution	EPREL data spectral diagram PROF LEDr 4000K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854071874	Folding box 1	112 mm x 112 mm x 248 mm	294.00 g	3.11 dm ³
4099854071881	Shipping box 6	356 mm x 242 mm x 278 mm	2195.00 g	23.95 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.