

## PRODUCT DATASHEET

### HQI-T 2000 W/D

POWERSTAR HQI®-T 1000...2000 W | Metal halide lamps for enclosed luminaires



#### Areas of application

- Factories and workshops
- Sports halls and multi-purpose halls
- Industrial installations
- Airports
- Docks and port facilities
- Marshaling yards, container transshipment facilities
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaires

#### Product benefits

- High efficiency
- E40 screw base for simple lamp handling
- UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter

#### Product features

- POWERSTAR® quartz technology
- Light colors: neutral white (N), daylight (D)



## TECHNICAL DATA

### Electrical data

Nominal wattage	2000 W
Nominal voltage	230 V
Ignition voltage	4.0/5.0 kVp <sup>1)</sup>
Operating mode	Conventional control gear (CCG) and ignitor
Nominal current	10.3 A
PFC capacitor at 50 Hz	85 µF
Rated lamp efficacy (HF data 25 °C)	85 lm/W

1) Minimum / Maximum

### Photometrical data

Luminous flux	180000 lm
Luminous efficacy	85 lm/W
Color temperature	7250 K
Color rendering index Ra	80
Light color	872
Rated lamp efficacy (HF data 25 °C)	85 lm/W
UV protection	Yes

### Dimensions & Weight

Overall length	430.00 mm
Length	430.00 mm
Light center length (LCL)	265,0 mm
Diameter	106.00 mm
Product weight	580.00 g

### Temperatures & operating conditions

Maximum permitted outer bulb temperature	500 °C
Maximum permitted base edge temperature	250 °C

### Lifespan

Lifespan B50	9000 h
--------------	--------

### Additional product data

Base (standard designation)	E40
-----------------------------	-----

Mercury content	170.0 mg
Design / version	Clear
Product remark	Not for general lighting






### Capabilities

Dimmable	No
Burning position	p30
Enclosed luminaire required	Yes
Hot restart	No

### Country-specific categorizations

ILCOS	MT/UB-2000/972-E/E/SL-E40-106/430/H
Order reference	HQI-T 2000W/D E

### DOWNLOAD DATA

Documents and certificates		Document name
	User Instruction	High Intensity Discharge Lamp UI
	Declarations of conformity	EC Declaration of Conformity - 2021 9C1-4082707-EN-00 - HQI 1000W-2000W
	Certificates	EAC RU C-DE.AYA46.B.16087_20 13.10.2020-12.10.2025 Rostest-Moskva - MH single capped
	Certificates	EAC N RU D-DE.MU62.B.00932_20 06.03.2020-05.03.2025 Prommash Test - MH
Photometric and lighting design files		Document name
	Spectral power distribution	502828_HQI_T_1000W_2000W_D

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321526809	Round wrap 1	465 mm x 130 mm x 130 mm	775.00 g	7.86 dm <sup>3</sup>
4008321526816	Shipping box 4	275 mm x 270 mm x 525 mm	3724.00 g	38.98 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.