

## PRODUCT DATASHEET

### HALOSTAR SST 2000 7 W 12 V G4

HALOSTAR® SUPERSTAR 2000 | Low-voltage halogen lamps with pin base



#### Areas of application

- General illumination
- Kitchen lighting
- Lighting for reading
- Entrance lighting
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings

#### Product benefits

- Brilliant accent lighting
- Significantly lower CO<sub>2</sub> emissions compared to standard version
- High luminous efficacy compared with standard lamps
- Incredibly small dimensions for revolutionary new luminaire designs
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter

#### Product features

- Average life: 2,000 h
- 100 % dimmable
- Color rendering index R<sub>a</sub>: 100
- Base: G4, GY6.35




## TECHNICAL DATA

### Electrical data

Nominal wattage	8 W
Construction wattage	8.00 W
Nominal voltage	12 V
Claimed equiv. conventional lamp power	10 W
Power factor $\lambda$	1.00

### Photometrical data

Luminous flux	95 lm
Luminous efficacy	11 lm/W
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	100
Light color	1027



349642\_HAL\_NV\_UVS

### Light technical data

Starting time	0 s
---------------	-----

### Dimensions & Weight

Overall length	33.00 mm
Light center length (LCL)	22,0 mm
Diameter	10,0 mm
Product weight	1.1 g

### Additional product data

Base (standard designation)	G4
-----------------------------	----

Mercury-free	Yes
Design / version	Tube

### Capabilities

Dimmable	Yes
Burning position	Any

### Certificates & Standards

Energy efficiency class	G
Energy consumption	8.00 kWh/1000h


### Country-specific categorizations

ILCOS	HSGST/UB-7-12-G4-22
Order reference	67416 ECO ST


### Energy labelling regulation data acc EU 2019/2015

Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G4
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	33.00 mm
Height	10,0 mm
Width	10,0 mm
Chromaticity coordinate x	0.460
Chromaticity coordinate y	0.411
Beam angle correspondence	SPHERE_360
EPREL ID	714442
Model number	AC35354

### DOWNLOAD DATA

Documents and certificates		Document name
	Declarations of conformity	CE Declaration HAL LOW VOLT

---

Photometric and lighting design files		Document name
	Spectral power distribution	349642_HAL_NV_UVS

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899195257	Blister 2	140 mm x 120 mm x 14 mm	13.20 g	0.24 dm <sup>3</sup>
4052899195264	Shipping box 20	164 mm x 148 mm x 130 mm	191.00 g	3.16 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.