



L	1270 mm
A	100 mm
H	100 mm

### ILLUMINOTECHNICAL CHARACTERISTICS

Luminous efficiency 100%.  
 Initial luminous flux of the luminaire 2956 lm.  
 Controlled direct symmetric distribution.  
 Installation Interdistance Transv.D = 1.77 x hu - Long.D = 1.17 x hu.  
 UGR <22 (EN 12464-1).  
 Luminous efficacy 134 lm/W.  
 Lifetime (L93/B50): 30000 h. (tq+25°C)  
 Lifetime (L90/B50): 50000 h. (tq+25°C)  
 Lifetime (L80/B50): 80000 h. (tq+25°C)  
 Lifetime (L80/B50): 50000 h. (tq+40°C)  
 Sudden decreased luminous flux after 50000 hours: 0% (C0).  
 Photobiological safety RGO, risk exempt, in compliance with IEC 62471, IEC/TR 62778.  
 In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards.

### SOURCE

Linear LED module 19W/840.  
 CIE 13.3 Color rendering index: CRI >80.  
 IES TM-30 Fidelity Index: Rf = 84 Rg = 95.  
 CCT nominal color temperature 4000 K.  
 Color initial tolerance (MacAdam): SDCM 3.

### MECHANICAL CHARACTERISTICS

Self-extinguishing V2 polycarbonate housing, injection moulded, RAL 7035 grey.  
 Ecologic anti-aging injected sealing gasket.  
 Diffuser in self-extinguishing V2 polycarbonate, photo-engraved interior, UV stabilised, injection moulded with smooth outer surface, tamper-proof opening.  
 Gear-tray reflector unit in hot-galvanized steel, painted in white polyester, fixed to the housing by means of steel rapid devices, hinged opening.  
 Snug fit snap-lock clips for diffuser mounting, in polycarbonate.  
 Possibility for technicians to access the interior of the luminaire.  
 Luminaire with limited surface temperature. - D -  
 Dimensions: 1270x100 mm, height 100 mm. Weight 2.049 kg.  
 IP65 protection degree.  
 Mechanical strength to impacts IK10 (20 joule).  
 Glow-wire test resistance 850°C.

### ELECTRICAL CHARACTERISTICS

Halogen Free electronic wiring 230V-50/60Hz, power factor >0.95, constant output current, SELV, class I, 1 driver.  
 Power of the luminaire 22 W.  
 CE - IEC 60598-1 - EN 60598-1.  
 Flicker: <4%.  
 Vac/Vdc driver suitable for EN 60598-2-22 emergency lighting systems, excluding high risk areas. The default power and flow are equal to 100% in AC and to 100% in DC.  
 Ambient temperature from -20°C to +40°C.  
 Relative humidity UR: <85%.

### INSTALLATION

Ceiling / Suspended / Wall.  
 All accessories dedicated to this product are available on the Catalog and on our website [www.3F-Filippi.com](http://www.3F-Filippi.com).

### SUPPLIED

Fixing brackets in stainless steel.

### APPLICATIONS

Product suitable for installation in food-production/processing environments (HACCP, IFS, BRC Standard).  
 Dry, dusty indoor environments, subject to occasional water splashes.  
 Virtually in all environments compatibly with the emissions/atmospheres compromising the use of plastic materials.  
 Not suitable for installation on surfaces subject to important vibrations, exposed to weather conditions, on ropes or poles.  
 Suitable for illumination of public car parks and parking grounds referred to DIN 67528:2018-04.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

Dimensions and specifications subject to alterations without notice.

ST.20201021 - Page 1 of 1

### 3F Filippi S.p.A.

Via del Savena 28, Z.I. Piastrella - 40065 Pian di Macina, Pianoro (Bologna), Italy  
 Tax Code. 01033260371 - VAT no. IT00529461204 - Share Capital € 3,000,000 fully paid up  
 Bologna Register of Companies no. 01033260371 - REA (economic administrative index) No. 234613

**Web** [www.3F-Filippi.com](http://www.3F-Filippi.com)  
**e-Mail** [3F-Filippi@3F-Filippi.it](mailto:3F-Filippi@3F-Filippi.it)  
**Telephone** +39.051.6529611  
**Fax** +39.051.775884