


0023252	<b>DATA SHEET</b>	
valid from: 01.01.2019	<b>ÖLFLEX® PETRO C HFFR multi core</b>	

## Application

ÖLFLEX® PETRO C HFFR - multi core is designed as connection and control cable especially for offshore applications like for instance on oil rigs for the cabling of pumping stations, compressors and generators of drilling units. The cable is UV-, oil-, MUD- and abrasion resistant for the use in harsh environment. The selected insulation and outer sheath compounds are halogen free and flame retardant resp. self-extinguishing.

The tinned copper braiding serves as screening against electrical interference. Depending on normative interpretation the braiding also can be used as so-called „Braid Armour“.

Use acc. to UL: PUR sheathed cable for external interconnection of electronic equipment.

Use acc. to cRU: PUR sheathed cable for external interconnection of electronic equipment with or without mechanical load conditions.

## Design

Design	according to UL AWM 20234, UL 758 based on DIN EN 50525-3-11 resp. VDE 0285-525-3-11
Certification	UL AWM Style 20234 (File No. E63634), UL 758 cRU AWM II A/B, (File No. E63634)
Conductor	fine wire strands of tinned copper acc. to IEC 60228 resp. VDE 0295, Class 5
Insulation	polyolefine compound, halogen free
Core identification code	acc. to VDE 0293-1, with or without GN/YE ground conductor up to 5 cores: acc. to VDE 0293-308 from 6 cores: black with white numbers acc. to DIN EN 50334 resp. VDE 0293-334
Stranding	cores twisted together into layers
Taping	non-woven wrapping
Inner sheath	halogen free special compound, colour: black, similar RAL 9005
Screen	braid of tinned copper wires, coverage = 85% (nominal value)
Outer sheath	special polymer compound, oil resistant, halogen free and flame retardant colour: black, similar RAL 9005 or blue, similar RAL 5015


## Electrical properties at 20°C

Rated voltage	U <sub>0</sub> /U: 600/1000 V
	UL/CSA: 1000 V
Test voltage	Core/Core: 4000 V AC
	Core/Screen: 4000 V AC

## Mechanical and thermal properties

Minimum bending radius	occasional flexing: 20 x outer diameter fixed installation: 6 x outer diameter
Temperature range	occasional flexing: -40 °C up to +90 °C max. conductor temp. occasional flexing (UL/CSA): +80 °C max. conductor temp. fixed installation: -50 °C up to +90 °C max. conductor temp. fixed installation(UL/CSA): up to +80 °C max. conductor temp.
Flammability	flame retardant in acc. with IEC 60332-1-2 resp. VDE 0482-332-1-2 UL: Vertical flame test VW-1 CSA: FT1 no flame-propagation acc. to IEC 60332-3-22 resp. VDE 0482-332-3-22 test cat. A
Halogen free	acc. to VDE 0472-815
UV resistance	acc. to EN 50618 resp. VDE 0283-618 acc. to EN 50620 resp. VDE 0285-620 acc. to EN ISO 4892-2-2013, method A (change of colour allowed)
Ozone resistance	acc. to EN 50396 resp. VDE 0473-396, method B
Oil resistance	acc. to EN 50363-10-2- resp. VDE 0207-363-10-2 and NEK TS 606: 2016
MUD resistance	acc. to NEK TS 606:2016 and IEC 61892-4, Annex D
Water-resistance	Salt water resistance acc. to UL 1309

Creator: LABU / PDC	Document: DB0023252EN	Page 1 of 2
Released: ALTE / PDC	Version: 05	

0023252	<b>DATA SHEET</b>	
valid from: 01.01.2019	<b>ÖLFLEX® PETRO C HFFR multi core</b>	

Tests

acc. to IEC 60811 resp. VDE 0473 part 811, EN 50395, EN 50396, UL 1581 and CSA C22.2

General requirements

These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive)

Creator: LABU / PDC	Document: DB0023252EN	Page 2 of 2
Released: ALTE / PDC	Version: 05	