


| | | |
|---------------------------|---|--|
| 0163007 | DATA SHEET |  |
| Valid from: 01.04.2019 | IEC compensating cable KP 4 L-SIL-S 2x1,5 oval | |

Application

The compensating cable KP 4 L-SIL-S 2 x 1,5 mm² is a silicone insulated cable which transmits the thermoelectric voltage of PtRh/Pt thermocouples. It is for flexible use and fixed installation in dry rooms with low mechanical load. They may only be installed outdoors with UV- and humidity protection and in observation of the max. permitted temperature range. The steel wire armoring serves as mechanical protection.

Design

| | | |
|---------------------|---|--------------------|
| Conductor | 1.5 mm ² (48 x 0.20 mm) | |
| Conductor material | RCB/SCB alloying, accuracy class 2 according IEC 60584 | |
| | Positive conductor: | Cu (copper) |
| | Negative conductor: | CuNi (cupronickel) |
| Core insulation | Silicone compound | |
| Core identification | Positive conductor: | orange |
| | Negative conductor: | white |
| Core layering | Cores parallel next to each other | |
| Outer sheath | Silicone compound, colour: | orange |
| Armouring | Galvanized steel wire braiding with interweaved, orange identification thread | |

Electrical properties

| | |
|----------------------------|---|
| Limiting deviation class 2 | ±60 µV (±5.0 °C) / measuring point temperature +1000 °C |
|----------------------------|---|

Mechanical and thermal properties

| | | |
|------------------------|---|----------------------|
| Temperature range | occasional flexing: | -25 °C up to +180 °C |
| Minimum bending radius | occasional flexing: | 15 x cable diameter |
| Flammability | flame retardant in acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2 | |

| | | |
|---|--------------------------------------|-------------|
| Creator: TOME/PCM Released: ALTE/PDC | Document: DB0163007EN Version: 02 | Page 1 of 1 |
|---|--------------------------------------|-------------|