


1312802	DATA SHEET	
valid from: 23.03.2020	ÖLFLEX® CLASSIC 400 P	

Application

ÖLFLEX® CLASSIC 400 P cables are oil resistant connection and control cables with a Polyurethan outer sheath, for flexible use and fixed installation for medium mechanical abuse. They are also suitable for use in dry, damp or wet areas. They are suitable for outdoor use if the indicated temperature range is observed.

ÖLFLEX® CLASSIC 400 P cables are increased resistant to oils and at room temperature largely resistant to acids and alkalis. The outer sheath withstands high mechanical stresses, in particular abrasion and dragging. It is also cut proof and resists microbes and hydrolysis. They are suitable for occasional, non-automated movements. The maximum tensile load is 15 N/mm² of conductor cross-section during installation and operation. Compulsory guidance is not permitted. Cables with black outer sheath are DESINA compliant.

Application range:

Industrial machinery, machine tools, measurement-, control-, electrical applications, food production and packaging machinery.

Design

Design	based on EN 50525-2-51 resp. VDE 0285-525-2-51 EN 50525-2-21 resp. VDE 0285-525-2-21
Conductor	fine wire strands of bare copper, acc. to IEC 60228 resp. VDE 0295, Class 5
Insulation	LAPP special PVC compound P8/1, better than the PVC compound T12, acc. to EN 50363-3 resp. VDE 0207-363-3
Core identification code	acc. to VDE 0293-1, with or without GN/YE ground conductor black cores with whit numbers acc. to DIN EN 50334 resp. VDE 0293-334
Outer sheath	Polyurethane compound TMPU acc. to EN 50363-10-2 resp. VDE 0207-363-10-2 colour: silver grey, similar RAL 7001 DESINA compliant, black, similar RAL 9005

Electrical properties at 20°C

Specific volume resistivity	> 20 GΩ x cm
Nominal voltage	U ₀ / U: 300 / 500 V
Test voltage	Core/Core: 4000 V AC

Mechanical and thermal properties

Minimum bending radius	occasional flexing: 12,5 x cable diameter fixed installation: 4 x cable diameter
Temperature range	occasional flexing: - 5 °C up to +70 °C max. conductor temp. fixed installation: - 40 °C up to +80 °C max. conductor temp.
UV resistance	acc. to EN 50618 resp. VDE 0283-618 acc. to EN 50620 resp. VDE 0285-620 acc. to EN ISO 4892-2-2013, method A (change of colour allowed)
Ozone resistance	acc. to EN 50396 resp. VDE 0473-396, method B
Oil resistance	acc. to EN 50363-10-2 resp. VDE 0207-363-10-2
Tests	acc. to IEC 60811, EN 50395, EN 50396
General requirements	These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive)
Environmental information	These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Creator: LABU / PDC	Document: DB1312802EN	Page 1 of 1
Released: ALTE / PDC	Version: 07	