



2173003	DATA SHEET	
valid from: 31.05.2023	UNITRONIC® TRAIN MVB 2x2x0,5mm² +4x0,25mm²	

Application

Field of use:	Flexible bus cable for the Multifunction Vehicle Bus (MVB) for serial data communication in railway vehicles. MVB is a component of the Train Communication Network (TCN) and standardized in IEC 61375-3-1.
Performance:	Screened foiled star quad cable, having a nominal impedance of 120 Ω. Designed for transmission rates of 1.5 Mbit/s. The MVB transmits time-critical control signals in real time.
Characteristics:	flame retardant, no flame propagation, halogen free, low smoke density, ozone resistant, UV resistant, oil resistant, fuel resistant, resistant to acids and alkalis
Applications:	MVB, TCN, RS-485 and others




Design

Certification	EN 45545-2: Hazard Level HL1, HL2, HL3 fire prevention acc. to NF F 16-101 Internal: Vehicle Categories A1, A2, B External: Vehicle Categories A2, B Category D for flame propagation Category F0 for smoke density
Conductor	Data pair: fine-wire stranded tinned copper 0.5 mm ² (19 x 0.185 mm) conductor diameter: ca. 0.92 mm Control cores: fine-wire stranded tinned copper 0.25 mm ² (19 x 0.127 mm) conductor diameter: ca. 0.61 mm
Insulation	Data pair: foamed polyolefine core diameter: ca. 2.3 mm Control cores: polyolefine core diameter: ca. 0.95 mm
Core identification code	Data pairs: red/blue, grey/brown Control cores: white/brown/green/yellow
Stranding	data cores twisted to star quad, with control cores applied to the interstices on top: plastic foil (overlapping)
Screen	plastic laminated aluminium foil (overlapping) on top: braid of tinned copper wires (coverage 85 % ± 5 %) diameter over braid: ca. 6.1 mm
Taping	thin non-woven tape (optional)
Outer sheath	cross-linked polymer compound, halogen free and flame retardant acc. to EN 50264-1, EM 104 black, similar RAL 9005 outer diameter: ca. 8.3 mm

Electrical properties at 20 °C

Conductor resistance	Data pair:	max. 40.1 Ω/km
	Control cores:	max. 79.9 Ω/km

Creator: KIOS / PDC	Document: DB2173003EN	Page 1 of 2
Released: ALTE / PDC	Version: 05	

2173003	DATA SHEET	
valid from: 31.05.2023	UNITRONIC® TRAIN MVB 2x2x0,5mm² +4x0,25mm²	

Insulation resistance	min. 5 GΩ x km	
Mutual capacitance	Data pair:	max. 46 nF/km (1.5 MHz)
Capacitive coupling	Data pair:	max. 1500 pF/km (1.5 MHz)
Characteristic impedance	Data pair:	120 Ω ±10% (0.75 MHz - 3 MHz)
Attenuation	Data pair:	max. 15 dB/km (1.5 MHz) max. 20 dB/km (3 MHz)
Near-end cross-talk	Data pair:	min. 45.0 dB/km (0.75 MHz - 3 MHz)
Velocity of propagation	Data pair:	0.74 c
Transfer impedance	max. 20 mΩ/m (20 MHz)	
Maximum operating voltage	125 V (not for power applications)	
Test voltage	core/core:	1000 V
	core/screen:	1000 V

Mechanical and thermal properties

Minimum bending radius	occasional flexing:	10 x outer diameter
	fixed installation:	3 x outer diameter
Temperature range	occasional flexing:	-35 °C up to +90 °C
	fixed installation:	-45 °C up to +90 °C
Burning load	0.43 kWh/m (calculated value)	
Flammability	flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2 flame propagation acc. to IEC 60332-3-25 resp. EN 60332-3-25	
Halogen free	acc. to IEC 60754-1 resp. EN 60754-1 acc. to EN 50264-1 appendix B	
Corrosivity of gases	acc. to IEC 60754-2 resp. EN 60754-2	
Smoke density	acc. to IEC 61034-2 resp. EN 61034-2	
Toxicity	acc. to EN 50305	
Weather and UV resistance	acc. to EN 50289-4-17 resp. VDE 0819-289-4-17 cables with black sheath are suitable for permanent outdoor use	
Ozone resistance	acc. to EN 50305	
Oil resistance	acc. to EN 50264-1, EM 104	
Fuel resistance	acc. to EN 50264-1, EM 104	
Tests	Test procedures for electrical characteristics and transmission characteristics acc. to EN 50288-1.	
General requirements	These cables are conform to the EU-Directive 2011/65/EU (RoHS, Restriction of the use of certain hazardous substances) and the LV-Directive 2014/35/EU (Low voltage Directive).	
Environmental information	These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).	

Creator: KIOS / PDC	Document: DB2173003EN	Page 2 of 2
Released: ALTE / PDC	Version: 05	