


2171055	<b>DATA SHEET</b>	
Valid from: 17.09.2018	<b>IE-PNC-5-M12D-S-(L*)-P-2-22-FD-OE</b>	

## Product description

Industrial Ethernet Patchcord, Profinet Type C, Cat.5, straight plug M12 on open conductor end , D-coded, PUR, for drag chain



This datasheet is also valid for other lengths configurations. Other lengths configurations on request

## Product variations

Article number	Article description	Length (L*) [m]
2171055	IE-PNC-5-M12D-S-1-P-2-22-FD-OE	1
2171056	IE-PNC-5-M12D-S-2-P-2-22-FD-OE	2
2171057	IE-PNC-5-M12D-S-3-P-2-22-FD-OE	3
2171058	IE-PNC-5-M12D-S-5-P-2-22-FD-OE	5
2171059	IE-PNC-5-M12D-S-10-P-2-22-FD-OE	10
2171060	IE-PNC-5-M12D-S-20-P-2-22-FD-OE	20


## General properties, Patchcord

Outer diameter, cable	6.5 mm
Number of cores	4
Outer sheath	PUR
Outer sheath, color	green similar to RAL 6018
Mating cycles, M12 connector	100
Screening	SF/UTP

## General properties, cable

LAPP-Article number of cable	2170894
LAPP-Description of cable	ETHERLINE FD P FC Cat. 5
Conductor, outer diameter	ca. 0.75 mm
Conductor, material	tinned copper, fine-wire stranded
Insulation, outer diameter	ca. 1.5 mm
Insulation, material	PE
Core identification code	acc. to IEC 708-1: white, yellow, blue, orange
Stranding	star quad
Wrapping	plastic tape plastic laminated aluminum foil
Screening	on top: braid of copper wire tinned wire, coverage ca. 85%

Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB2171055EN Version: 05	Page 1 of 3
---	--------------------------------------	-------------

2171055	<b>DATA SHEET</b>	
Valid from: 17.09.2018	<b>IE-PNC-5-M12D-S-(L*)-P-2-22-FD-OE</b>	

### Electrical properties, cable at 20°C

Resistance (loop)	≤ 120 Ω/km
Insulation material, specific electrical resistance	≥ 0.5 GΩ*km
Characteristic impedance (1 MHz to 100 MHz)	100 Ω ± 15 Ω
Signal propagation time	< 5.3 ns/m
Test voltage (rms 50 Hz, 1 min.), core-core	700 V
Test voltage (rms 50 Hz, 1 min.), core-screening	700 V

### Mechanical and thermal properties, cable

Minimum bending radius, during laying	8 x cable diameter
Minimum bending radius, fixed installation	5 x cable diameter
Permissible temperature range, during laying	-20 °C to +60 °C
Permissible temperature range, fixed installation	-30 °C to +70 °C
Sunlight resistance	sunlight resistant acc. to UL 1581 Sec. 1200
Flame propagation	flame retardant acc. to UL 1581 (VW-1)
Halogen free	halogen free acc. to VDE 0472-815
General requirements	Dangerous and forbidden substance acc. to RoHS directive (2002/95/EG) are not allowed to the manufacturing

### General properties, M12 connector

Coding	D
Protection degree	IP67/IP69 locked connector
Rated voltage max.	250 V
Rated current at 40 °C	4 A
Ambient temperature	-30 °C to +90 °C
Insulation resistance	≥ 10 <sup>8</sup> Ω
Locking nut with vibration protection	Yes
Tightening torque	1.0 Nm

### Materials, M12 connector

Contacts, base material	CuZn
Contacts, surface	Au
Grip body	TPU
Locking nut, base material	CuZn


### Standards

Product standard, M12 connector	DIN EN 61076-2-101
---------------------------------	--------------------

### Approvals

UL-listed, E-File	E249137
-------------------	---------



Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB2171055EN Version: 05	Page 2 of 3
---	--------------------------------------	-------------

2171055	<b>DATA SHEET</b>	
Valid from: 17.09.2018	IE-PNC-5-M12D-S-(L*)-P-2-22-FD-OE	

**Drawings**



**Contact Configuration**



**Application range**

Automation, industrial machinery and plant engineering

**Note**

Photographs are not true to scale and do not represent detailed images of the respective products.

Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB2171055EN Version: 05	Page 3 of 3
---	--------------------------------------	-------------