

44420128	<b>DATA SHEET</b>	
Valid from: 17.09.2018	<b>EPIC<sup>®</sup> M23 SIGNAL M23 17E/P D-SUB</b>	

## Description

- Inserts for M23 circular connectors
- Efficient assembling due to the use of D-Sub contacts-on-reel



## General characteristics

Series	SIGNAL M23
Version	E-part = rotation to the right (clockwise) / P-part = rotation to the left (anticlockwise)
Pins	17
Termination method	Crimp termination
Termination cross-section	0,08 - 0,56 mm <sup>2</sup>
Temperaturbereich	-25 to +125 °C
Contacts included	no

## Product variations

Article no.	Version	Suitable contacts	PU
44420128	E-Part	male D-Sub crimp-contacts on reel	5
44420129	E-Part	male D-Sub crimp-contacts on reel	20
44420130	E-Part	female D-Sub crimp-contacts on reel	5
44420131	E-Part	female D-Sub crimp-contacts on reel	20
44420132	P-Part	male D-Sub crimp-contacts on reel	5
44420133	P-Part	male D-Sub crimp-contacts on reel	20
44420134	P-Part	female D-Sub crimp-contacts on reel	5
44420135	P-Part	female D-Sub crimp-contacts on reel	20

## Mechanical characteristics

Cycles of mechanical operation	50
--------------------------------	----

## Electrical characteristics

Rated Voltage, IEC	50 V
Rated Impulse Voltage	0,8 kV
Rated Current	4 A
Contact Resistance	< 4 mOhm
Degree of Soiling	3

## Materials and surfaces

Contacts	Partly gold-plated brass
----------	--------------------------



## Standards

Safety Standard	IEC 61984
-----------------	-----------

Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB44420128EN Version: 02	Page 1 of 3
---	---------------------------------------	-------------

44420128	<b>DATA SHEET</b>	
Valid from: 17.09.2018	<b>EPIC<sup>®</sup> M23 SIGNAL M23 17E/P D-SUB</b>	

### Drawings



Good chemical resistance



Industrial machinery and plant engineering



Mechanical resistance



Assembly time



Robust



Wind Energy



Variety of approval certifications

Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB44420128EN Version: 02	Page 2 of 3
---	---------------------------------------	-------------

44420128	<b>DATA SHEET</b>	
Valid from: 17.09.2018	<b>EPIC<sup>®</sup> M23 SIGNAL M23 17E/P D-SUB</b>	

### Info

For D-Sub ribbon contacts

### Application range

Plant engineering

Measurement and control technology

Apparatus construction

### Remark

The inserts are suitable for both male and female contacts. For a complete connection, you will need one P-component and one E-component. P-component = left turning (anticlockwise), E-component = right turning (clockwise)

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB44420128EN Version: 02	Page 3 of 3
---	---------------------------------------	-------------