

55507040	DATA SHEET	
Valid from: 03.07.2018	SILVYN® REC	

SILVYN® REC is an end-cap for SILVYN® FPAS conduits.



Material: TPE

Features: Fast assembling
For fine or coarse pitch conduits
Prevent cable damage
Oil-Resistant

Temperature range: -50°C up to +120°C

Colour: Black (UV-Resistant)

Norm Reference: 

Note: Free of halogen, Sulphur and phosphorus

Protection class: Up to IP68 dependent on cable

Dimension table:

Part no.	Part name	Conduit Ø mm	Total height mm	Article Designation mm	Clamping range mm
5550 7040	SILVYN® REC	10	27	20,5	3,0 - 7,0
5550 7041	SILVYN® REC	13	27	20,5	3,0 - 7,0
5550 7042	SILVYN® REC	16	33,6	22,7	3,0 - 11,0
5550 7043	SILVYN® REC	21	38,3	28,4	3,0 - 15,0
5550 7044	SILVYN® REC	28	40,8	36,2	3,0 - 21,0
5550 7045	SILVYN® REC	34	42,3	42,5	3,0 - 25,0
5550 7046	SILVYN® REC	42	47	51,3	3,0 - 34,0
5550 7047	SILVYN® REC	54	51,9	63,1	3,0 - 46,0



For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB55507040EN Version: 01	Page 1 of 1
---	---------------------------------------	-------------