


55502431	<b>DATA SHEET</b>	
Valid from: 03.07.2018	<b>SILVYN® MPC 45° M</b>	

The SILVYN® MPC 45° M is a polyamide conduit gland for smooth and corrugated conduits. The 45° angle with integrated conduit connection enables best assembling.



- Material:** PA 66
- Features:** Dust protection  
Moisture protection  
Tensile strength
- Resistance:** To oil
- Temperature range:** -40°C up to +120°C
- Colour:** Black (UV-Resistant)  
Grey (RAL 7001)

**Norm Reference:**




**Notes:** Free of halogen, Phosphor and Sulphur

**Protection class:** IP 65 with wavy conduits  
IP 67 with smooth conduits

**Dimensions table:**


Part No.	Part name	Total length mm	Smallest inner Ø mm	Largest outer Ø mm	Length of thread mm	Seat area Ø mm
<b>black</b>						
5550 2431	SILVYN® MPC 45° M 20x1,5/1	45	10,5	28	13	27
5550 2432	SILVYN® MPC 45° M 20x1,5/2	47	14,5	33	13	27
5550 2433	SILVYN® MPC 45° M 25x1,5	55	19	42	15	33
5550 2434	SILVYN® MPC 45° M 32x1,5	64	24,5	48	16	40
<b>grey</b>						
5550 2435	SILVYN® MPC 45° M 20x1,5/1	45	10,5	28	13	27
5550 2436	SILVYN® MPC 45° M 20x1,5/2	47	14,5	33	13	27
5550 2437	SILVYN® MPC 45° M 25x1,5	55	19	42	15	33
5550 2438	SILVYN® MPC 45° M 32x1,5	64	24,5	48	16	40

55502431	<b>DATA SHEET</b>	
Valid from: 03.07.2018	<b>SILVYN® MPC 45° M</b>	

**Suitable:**

- SILVYN® EL waved/smooth
- SILVYN® ELU waved/smooth
- SILVYN® ELÖ waved/smooth
- SILVYN® ELT waved/smooth
- SILVYN® ELR smooth

**Allocation table:**

<b>Conduit</b>	 <p><b>SILVYN® EL/ELÖ/ELT/ELR/ELU</b></p>
SILVYN® MPC 45° M 20x1,5/1	16
SILVYN® MPC 45° M 20x1,5/2	20
SILVYN® MPC 45° M 25x1,5	25
SILVYN® MPC 45° M 32x1,5	32

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Auch /PDP Released: DAMU1/PDP	Document: DB55502431EN Version: 01	Page 2 of 2
--	---------------------------------------	-------------