


55501982	DATA SHEET	
Valid from: 03.07.2018	SILVYN® LGS-2-M	

SILVYN® LGS-2-M is a two part conduit gland made of nickel plated brass for swivel applications.

The conduit gland can be used in outdoor areas and in mechanical demanding environments.



Material: Brass, nickel plated

Features: High tensile strength
Oil resistant
Corrosion resistant

Temperature range: -50°C up to +300°C

Norm Reference:



Protection class: IP 54

Dimension table:

Part No.	Description	NW	Thread	Inner Ø mm	Thread length mm	Length mm	SW
5550 1982	SILVYN® LGS-2-M 12x1,5	10	M12x1,5	5,6	8,0	30,2	13
5550 2003	SILVYN® LGS-2-M 16x1,5/1	12	M16x1,5	8,5	8,0	32,2	17
5550 2004	SILVYN® LGS-2-M 16x1,5/2	16	M16x1,5	11,5	10,0	34,2	20
5550 2023	SILVYN® LGS-2-M 20x1,5/1	16	M20x1,5	11,5	10,0	34,2	22
5550 2024	SILVYN® LGS-2-M 20x1,5/2	20	M20x1,5	15,3	10,0	35,5	24
5550 2032	SILVYN® LGS-2-M 25x1,5	25	M25x1,5	19,1	12,0	43,7	29
5550 2042	SILVYN® LGS-2-M 32x1,5	32	M32x1,5	26,2	13,0	48,0	38
5550 2052	SILVYN® LGS-2-M 40x1,5	40	M40x1,5	34,2	14,0	51,2	48
5550 2062	SILVYN® LGS-2-M 50x1,5	50	M50x1,5	44,8	15,0	54,2	58
5550 2072	SILVYN® LGS-2-M 63x1,5	63	M63x1,5	54,5	18,0	63,2	70

Suitable conduit: SILVYN® LCC-2
SILVYN® LCCH-2

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB55501982EN Version: 01	Page 1 of 1
---	---------------------------------------	-------------