


55501640	<b>DATA SHEET</b>	
Valid from: 03.07.2018	<b>SILVYN® HG-M / HW-M</b>	

SILVYN® GH-M and HW-M are conduit glands for the corrugated conduit SILVYN® HCC. Die gland has a quick mounting system for a quick and easy assembling and disassembling. The connection has a high tensile strength and thickness.

- Material:** PA 6
- Features:** Quick and easy assembling and disassembling  
Tensile strength
- Temperature range:** -25°C up to +105°C
- Colour:** Black (UV-Resistant)
- Note:** Free of halogen
- Protection class:** IP65



**Dimension table:**

Part No.	Part name	Thread	Length mm	Thread Length mm	Diameter mm	SW
<b>SILVYN® HG-M</b>						
5550 1600	SILVYN® HG-M 12x1,5 BK	M12x1,5	26,3	8	21	21
5550 1610	SILVYN® HG-M 16x1,5 BK	M16x1,5	29,4	10,5	24,7	25
5550 1620	SILVYN® HG-M 20x1,5 BK	M20x1,5	36	12	29,8	30
5550 1630	SILVYN® HG-M 25x1,5 BK	M25x1,5	45,4	15	37,2	38
5550 1640	SILVYN® HG-M 32x1,5 BK	M32x1,5	47	15	45	45
5550 1650	SILVYN® HG-M 40x1,5 BK	M40x1,5	53	15	56,2	57
5550 1660	SILVYN® HG-M 50x1,5 BK	M50x1,5	57,4	15	68	68
5550 1670	SILVYN® HG-M 63x1,5 BK	M63x1,5	74	20	82	82
<b>SILVYN® HW-M</b>						
5550 1680	SILVYN® HW-M 12x1,5 BK	M12x1,5	36,3	8	21	21
5550 1690	SILVYN® HW-M 16x1,5 BK	M16x1,5	42,9	10,5	24,7	25
5550 1700	SILVYN® HW-M 20x1,5 BK	M20x1,5	51,5	12	29,8	30
5550 1710	SILVYN® HW-M 25x1,5 BK	M25x1,5	64,4	15	37,2	38
5550 1720	SILVYN® HW-M 32x1,5 BK	M32x1,5	75	15	45	45

**Suitable for:** SILVYN® HCC

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB55501640EN Version: 01	Page 1 of 1
-------------------------------------------------	---------------------------------------	-------------