

61802080	<b>DATA SHEET</b>	
Valid from: 18.04.2019	<b>SILVYN® AS</b>	

The protection conduit SILVYN® AS is a strip-wound metal conduit with hooked, polygonal profile and round cross section. SILVYN® AS is an electrical installation conduit with the structural shape G acc. to DIN 49012 and tested to DIN EN IEC 61386-23.

The Conduit can be used in the automotive, shipbuilding, automation and much more.



**Material:**

Galvanized steel

**Technical features:**

Profile

Strip wound metal conduit with hooked profil

Nominal width

NW 10 up to NW 56

Protection class

IP40 acc. to EN 60529

Depending on the used conduit gland

Temperature range

-50°C up to +250°C

**Additional features:**

Compressive strength

Class 3 (750N) acc. to EN 61386

Impact strength

Class 3 (2kg / 100mm) acc. to EN 61386

Bending resistance

Flexible

Tensile strength

Class 3 (500N) acc. to EN 61386

**Approvals:**



**Reference standards:**

DIN EN 61386-23

**Suitable glands:**

SILVYN® MSK-M US  
SILVYN® US  
SILVYN® US-M  
SILVYN® US-AS

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: MAU1 /PDP Released: DAMU1/PDP	Document: DB61802080EN Version: 07	Page 1 of 2
---	---------------------------------------	-------------

61802080	<b>DATA SHEET</b>	
Valid from: 18.04.2019	SILVYN® AS	

**Dimension table:**

Part No.	NW	Diameter mm		Max. Bending radius mm		Weight kg/m
		Inner	Outer	static	dynamic	
6180 2080	10	8,0	10,0	20	50	0,05
6180 2090	14	11,0	14,0	28	70	0,12
6180 2100	17	14,0	17,0	30	75	0,14
6180 2110	19	16,0	19,0	35	90	0,15
6180 2120	21	18,0	21,0	40	100	0,21
6180 2130	27	23,0	27,0	48	120	0,26
6180 2140	36	31,0	36,0	60	150	0,48
6180 2150	45	40,0	45,0	82	205	0,62
6180 2170	56	51,0	56,0	100	250	0,80

Creator: MAU1 /PDP Released: DAMU1/PDP	Document: DB61802080EN Version: 07	Page 2 of 2
---	---------------------------------------	-------------