


65500475	DATA SHEET	
Valid from: 03.07.2018	SILVYN® FLEXILOK PG	

SILVYN® FLEXILOK PG is a one-part conduit gland with fast fit for a safety assembling. For the demounting you are using a screwdriver. The gland is suitable for SILVYN® FPAS and can be used in the machine- and plant constructions, control cabinet and building wiring.



Material: PA66

Features: Fast assembling
Slim design
Suitable for fine and coarse conduits

Temperature range: -40°C up to +120°C

Colour: Grey (RAL 7031)
Black (UV-Resistant)

Norm reference:  
UL FILENUMBER E308201

Note: Free of halogen, silicon and cadmium

Protection class: IP 66

Dimension table:

Part no.	Part name	Thread	Conduit Ø mm	Total length mm	Thread length mm	Outer Ø mm	Inner Ø mm
Black							
6550 0475	SILVYN® FLEXILOK PG	PG 9/1	13	41	10	20	11,5
6550 0495	SILVYN® FLEXILOK PG	PG 9/2	16	42	10	23	11,5
6550 0485	SILVYN® FLEXILOK PG	PG 11/1	13	41	10	20	11,5
6550 0395	SILVYN® FLEXILOK PG	PG 11/2	16	42	10	23	14,5
6810 0055	SILVYN® FLEXILOK PG	PG 13,5/1	16	42	10	23	15,5
6810 0075	SILVYN® FLEXILOK PG	PG 13,5/2	21	45	10	29	16
6810 0065	SILVYN® FLEXILOK PG	PG 16/1	16	43	11	23	15,5
6810 0085	SILVYN® FLEXILOK PG	PG 16/2	21	46	11	29	17,5
6810 0095	SILVYN® FLEXILOK PG	PG 21	28	51	12	36	22,5
6888 0005	SILVYN® FLEXILOK PG	PG 29	34	54	12	43	30,5
Grey							
6550 0470	SILVYN® FLEXILOK PG	PG 9/1	13	41	10	20	11,5
6550 0490	SILVYN® FLEXILOK PG	PG 9/2	16	42	10	23	11,5
6550 0480	SILVYN® FLEXILOK PG	PG 11/1	13	41	10	20	11,5
6550 0390	SILVYN® FLEXILOK PG	PG 11/2	16	42	10	23	14,5
6810 0050	SILVYN® FLEXILOK PG	PG 13,5/1	16	42	10	23	15,5
6810 0070	SILVYN® FLEXILOK PG	PG 13,5/2	21	45	10	29	16
6810 0060	SILVYN® FLEXILOK PG	PG 16/1	16	43	11	23	15,5
6810 0080	SILVYN® FLEXILOK PG	PG 16/2	21	46	11	29	17,5
6810 0090	SILVYN® FLEXILOK PG	PG 21	28	51	12	36	22,5
6550 0620	SILVYN® FLEXILOK PG	PG 29	34	54	12	43	30,5

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB65500475EN Version: 01	Page 1 of 1
---	---------------------------------------	-------------