


65500405	DATA SHEET	
Valid from: 03.07.2018	SILVYN® FLEXILOK M	

Dimension table:

Part no.	Thread	Conduit Diameter mm	Total length mm	Thread length mm	Outer Diameter mm	Inner Diameter mm
SILVYN® FLEXILOK M Black						
6550 0403	M 12x1,5	10	35	9	16	8
6550 0405	M 16x1,5/1	13	43	12	20	11
6550 0425	M 16x1,5/2	16	45	12	23	11
6550 0415	M 20x1,5/1	13	44	14	20	11
6550 0435	M 20x1,5/2	16	46	14	23	14,5
6550 0445	M 20x1,5/3	21	49	14	29	14,5
6550 0455	M 25x1,5	28	54	15	36	19,5
6550 0465	M 32x1,5	34	58	16	43	26,5
6550 0458	M 40x1,5	42	63	16	54	32,5
6550 0459	M 50x1,5	54	70	16	68	42
6550 0468	M 63x1,5	54	70	16	68	53
SILVYN® FLEXILOK M Grey						
6550 0404	M 12x1,5	10	35	9	16	8
6550 0600	M 16x1,5/1	13	43	12	20	11
6550 0420	M 16x1,5/2	16	45	12	23	11
6550 0410	M 20x1,5/1	13	44	14	20	11
6550 0430	M 20x1,5/2	16	46	14	23	14,5
6550 0440	M 20x1,5/3	21	49	14	29	14,5
6550 0610	M 25x1,5	28	54	15	36	19,5
6550 0460	M 32x1,5	34	58	16	43	26,5
6550 0466	M 40x1,5	42	63	16	54	32,5
6550 0467	M 50x1,5	54	70	16	68	42
6550 0469	M 63x1,5	54	70	16	68	53

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB65500405EN Version: 04	Page 2 of 2
---	---------------------------------------	-------------