


<b>7038885</b>	<b>DATA SHEET</b>	
<b>valid from: 06.02.2019</b>	<b>UNITRONIC® SENSOR FD Li9YC11Y</b>	

## Application

UNITRONIC® SENSOR FD Li9YC11Y are sensor/actuator cables, designed for applications in power chains.

## Design

Design	based on UL AWM Style 10493 (Insulation) and 20549 (Jacket), UL 758, CSA C22.2 No. 210 (80°C, 300 V)
Certification	UL AWM Style 20549 (File No. E63634), UL 758 cRUus AWM I/II A/B (File No. E63634)
Conductor	superfine wire strands of bare copper wires
Insulation	polypropylene
Core identification code	according to EN 60947-5-2 3-core: brown, blue, black 4-core: brown, white, blue, black 5-core: brown, white, blue, black, grey
Stranding	cores stranded to bundle, talced 5-core: central filler wrapping with non-woven tape
Screen	braid of tinned copper wire, coverage ca. 85 %
Outer sheath	PUR Colour: black (similar RAL 9005)

## Diameter of the outer sheath

Article number	Dimension	Outer sheath $\varnothing$
7038885	3x0.34 mm <sup>2</sup>	ca. 4.3 mm
7038886	4x0.34 mm <sup>2</sup>	ca. 4.6 mm
7038887	5x0.34 mm <sup>2</sup>	ca. 5.0 mm

## Electrical properties at 20°C

Conductor resistance	0.34 mm <sup>2</sup> : max. 57 $\Omega$ /km
Specific volume resistivity	7x10 <sup>15</sup> $\Omega$ x cm
Peak operating voltage	300 V (not for power applications)
Test voltage	C/C: 2000 V C/S: 2000 V

## Mechanical and thermal properties

Minimum bending radius	Flexing: 10 x cable $\varnothing$ Fixed installation: 5 x cable $\varnothing$
Temperature range	VDE: Flexing: -25°C up to +80°C Fixed installation: -40°C up to +80°C UL AWM: up to +80°C
Number of cycles	min. 4 mio. alternating bending cycles (max. 60°C)
Travel distance	10 m length, min. 10 x cable $\varnothing$ , max. 3 m/s, max. 10 m/s <sup>2</sup>
Flammability	flame retardant acc. to UL 1581 FT-2
Halogen free	according to VDE 0472-815
General requirements	This cable is conform to the EU-Directive 2011/65/EU (RoHS, Restriction of the use of certain hazardous substances).

Creator: PESA / PDC	Document: DB7038885EN	Page 1 of 1
Released: ALTE / PDC	Version: 04	